

DATASHEET

Taubmans Armawall Moroka Bag & Paint Top Coat

TAUBMANS

Product Code:
303200



Taubmans Armawall Moroka Bag & Paint Top Coat

Taubmans Moroka is a durable exterior acrylic designed to give a medium profile "bag and paint" effect. Moroka Bag and Paint bridges hairline cracks in masonry surfaces. May be applied by "mitt" to create decorative bag and paint effects.

Resists efflorescence when used in combination with Moroka Wall Treatment.



USES

Recommended for use on flush mortar brick walls, and is also suitable for concrete and cement render.

FEATURES AND BENEFITS

MOULD RESISTANT	Helps resist the growth of mould, mildew and fungus
WEATHER RESISTANCE	Provides advanced protection against the extremes of weather
FLEXIBLE	Withstands normal substrate movements
SEAMLESS MEMBRANE	A highly flexible acrylic seamless membrane with outstanding weather and moisture resistance
RESISTS EFFLORESCENCE	Resists the salt staining effects of efflorescence
UV PROTECTION	Blocks out harmful UV rays for longer lasting results
WATER BASED FORMULA	Easy clean up with water
FLAT FINISH	Gives a flat finish with excellent surface defect hiding properties.
TINTABLE	Tintable to over 10,000 colours. Order A4 samples or brush outs online at https://www.taubmans.com.au/specifiers/explore#search
VAPOR PERMEABILITY	Allows substrate to breathe to reduce moisture entrapment

DATASHEET

MEDIUM TEXTURE PROFILE	Contemporary bag and paint finish
ABRASION RESISTANCE	
ACRYLIC BINDER	Acrylic technology for advanced protection against harsh weather conditions and excellent resistance to peeling and cracking.

PRODUCT SPECIFICATIONS

DRY TIMES: RECOAT	4 hours
15L AVAILABLE SIZES	15L
SDS	SDS available at www.ppgmsds.com.au
EXTENSIVE COLOUR RANGE	Tintable to over 10,000 colours. Order A4 samples or brush outs online at https://www.taubmans.com.au/specifiers/explore#search
WHITE BASE	Tint your desired colour from a White base
ACCENT BASE	Tint your desired colour from an Accent base
GLOSS LEVEL	Armawall Moroka gives a Flat finish with a 2% gloss level
WET FILM THICKNESS	400 microns
DRY FILM THICKNESS	220 microns

SURFACE PREPARATION

BRICK & BLOCK	Exterior walls, bricks, blocks, concrete, cement render, and masonry walls. Moroka is recommended for use on flat surface or flush mortar brick wall for optimal finish appearance.
NEW WORK	<p>Fresh cementitious substrates should be left to cure for 28 days before painting. There must be less than 15% moisture content at the surface prior to and during application.</p> <p>All surfaces must be free of dirt, dust, grease, oil, mould release agents, bond breakers and any other contaminants that may interfere with adhesion.</p> <p>Surface irregularities such as blow holes and profile defects may require patching with Armawall Smooth Patch or Armawall Coarse Patch prior to system application.</p> <p>Moroka Bag and Paint must be applied over Moroka Wall Treatment to give maximum resistance to efflorescence.</p>
PREVIOUSLY PAINTED	Previously painted surfaces in sound condition should be scrubbed down with detergent and fresh water, washed with clean water and allowed to dry.

APPLICATION

LAMBS WOOL MITT	Yes
AIRLESS SPRAY	AIRLESS SPRAY
BRUSH	Stir paint in a circular lifting motion for 5 minutes before use. Apply one or two coats (as per recommendation), with the recommended RECOAT time between each coat (refer to product spec). Paint the corners and edges with a narrow brush. Avoid using poor quality or worn brushes as they can adversely affect the final finish.

DATASHEET

COARSE TEXTURE ROLLER	Yes
NAP ROLLER	16mm -22 mm Pile Roller
COVERAGE	2 - 3 m ² /litre
COATS REQUIRED	Two
CONCRETE	<p>New cement render, masonry and concrete surfaces should be allowed to cure for 28 days. Off form concrete should be thoroughly cleaned by acid etching, water or sand blasting to ensure all bond breaker oils are removed.</p> <p>Concrete and masonry surfaces in sound condition must be thoroughly clean and free from mould.</p> <p>Surface irregularities such as blow holes and profile defects may require patching with Taubmans Armawall Smooth or Coarse Patch prior to Moroka system application.</p> <p>Treat the substrate with Armawall Moroka Bag & Paint Treatment allow two hours to dry before applying Moroka Bag & Paint Top Coat.</p>
PREVIOUSLY COATED	Remove all loose and flaking paint away to bare substrate before re-coating.
STIRRING	Stir Moroka Bag and Paint thoroughly prior to use
APPLICATION	Apply 1 or 2 coats as required of Moroka Bag and Paint using a long nap roller. Apply by mitt in a circular motion to create bag and paint effect.

PRECAUTIONS

GENERAL SAFETY INFORMATION	<p>WALL PAINTS</p> <p>SAFETY</p> <p>Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p> <p>CEILING</p> <p>SAFETY</p> <p>Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p>
FIRST AID INFORMATION	<p>IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.</p> <p>EYE CONTACT - Flush with plenty of water. Always seek medical advice.</p> <p>SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.</p> <p>INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.</p> <p>AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au</p>
ENVIRONMENT INFORMATION	Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au
GENERAL	<ul style="list-style-type: none"> • Avoid painting when the substrate or ambient temperature is less than 10C or greater than 35C • Not suitable for timber or metal substrates • When applying Moroka Bag and Paint on large or unbroken high rise off form concrete, you will not easily be able to maintain a wet edge. This can cause overlaps to stand out.

DATASHEET

PRODUCT DESCRIPTION**10 YEAR GUARANTEE
MOROKA**

Taubmans guarantees that Moroka Wall Treatment used with Moroka Bag & Paint will not blister, flake or peel for 10 years, provided it is applied on properly prepared sound new surfaces according to printed label directions. This guarantee does not cover paint failure caused by breakdown of a previously applied coating. If Taubmans Moroka does not perform as specified above, Taubmans will provide free of charge paint to rectify the affected areas.

VERSION**VERSION DATE** July 2024**VERSION NUMBER** 1.0**DISCLAIMER**

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACTTaubmans Customer Service: 131 686 Further information: www.taubmans.com.au