

DATASHEET

Taubmans Fast Drying Stain Blocker

TAUBMANS

Product Code:
111531



Taubmans Fast Drying Stain Blocker

Taubmans Fast Drying Stain Blocker is an incredibly quick drying high performance prep coat. The shellac based formula is perfect for sealing persistent water based stains and blocking odours and tannin bleed. Suitable for use on smoke or water damaged surfaces, or areas where odour sealing is required. The foundation for a perfect finish.

USES

Suitable for use on previously painted surfaces, tannin-rich timbers, MDF, bricks, and masonry.

FEATURES AND BENEFITS

AUSTRALIAN MADE	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
FAST DRYING	Assist project completion timelines with fast drying properties
STAIN BLOCKER	Excellent stain suppressing and sealing qualities. Effectively seals stains and provides a sound surface for top coats
EXCELLENT ADHESION	Provides excellent adhesion to difficult surfaces.
TANNIN BLOCKER	A barrier coating that effectively blocks and prevents tannin bleed on tannin-rich timbers

PRODUCT SPECIFICATIONS

CLEAN UP	Methylated Spirits
300GM AVAILABLE SIZES	300gm
1L AVAILABLE SIZES	1l
4L AVAILABLE SIZES	4l
SDS	SDS available from the Taubmans Website taubmans.com.au

DATASHEET

GLOSS LEVEL	Flat
WET FILM THICKNESS	80µm
DRY FILM THICKNESS	25µm
DRY TIMES: TOUCH DRY	15 minutes
DRY TIMES: RECOAT	45 minutes
VOC LEVELS	<525 g/L

Surface Preparation

SHELLAC - PREPARATION	Surfaces must be clean, dry and free from all surface contamination. For mould-based stains, use Taubmans Advanced Adhesion Mould Blocker. For ink or marker stains use Taubmans Tough Stain Blocker. Remove stains as much as possible by sanding, scraping and washing. Rinse with water and allow to dry. Fill in the surface defects with suitable filler, putty or sealant. Always test stain blocking and adhesion on a small area prior to commencing project.
------------------------------	--

APPLICATION

BRUSH OR ROLLER	Apply one or two coats (as per recommendation) by brush or roller, with the recommended recoat time between each coat (refer to product spec). Paint corners and edges with a narrow brush. Roll up to the edges using a quality roller with the recommended nap (refer to product spec).
AEROSOL	AEROSOL
COATS REQUIRED	1
NAP ROLLER	12-16mm
COVERAGE	Up to 14m ² /L
STIRRING RECOMMENDATION	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. Continue stirring at regular intervals during application.
APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS	10
APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS	30

PRECAUTIONS

DANGER FLAMMABLE LIQUID AND VAPOUR	Warning. Flammable hydrocarbon liquid. Keep out of reach of children. Keep lid on when not in use. Wear solvent resistant gloves and eye protection when using. Ensure adequate ventilation and do not breathe vapour.
GENERAL SAFETY INFORMATION	WALL PAINTS SAFETY Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water

DATASHEET

after use.

CEILING

SAFETY

Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

FIRST AID INFORMATION

IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.

EYE CONTACT - Flush with plenty of water. Always seek medical advice.

SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.

INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.

AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686
Further information: www.taubmans.com.au

ENVIRONMENT INFORMATION

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au