

DATASHEET

Taubmans Tradex Sanding Sealer

TAUBMANS

Product Code:
274517

Taubmans Tradex Sanding Sealer

Taubmans Tradex Sanding Sealer is a polyurethane-based sealer designed to be applied to bare or stained interior timber surfaces prior to finishing. Provides an easily sanded film to fill grain prior to application of Clearproof Interior polyurethanes.



USES

Interior. Bare or stained interior timber surfaces such as doors, trims and windows.

FEATURES AND BENEFITS

EASY TO APPLY	Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.
PENETRATIVE FORMULA	Low viscosity and excellent wetting properties allow the coating to penetrate the surface.
AUSTRALIAN MADE	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.

PRODUCT SPECIFICATIONS

CLEAN UP	Mineral turps
FLAT	Designed to produce flat uniform finish with no roller marks
GLOSS LEVEL	1-2 (% at a 60 degree angle)
VOC LEVELS	472g/Litre
DRY TIMES: TOUCH DRY	120 mins
DRY TIMES: RECOAT	16 hours
4L AVAILABLE SIZES	4l

DATASHEET

SDS SDS available from the Taubmans Website taubmans.com.au

SURFACE PREPARATION

GENERAL INTERIOR	Can include interior walls, ceilings, doors and architraves
NEW WORK	<p>TIMBER Weathered (greyed) timber must be sanded to the original timber surface. Tannin rich timbers such as cedar may require two coats or use Taubmans Oil Based Wood Primer.</p> <p>GALVANISED IRON Thoroughly degrease new surfaces. Weathered surfaces should be thoroughly cleaned before painting. For structural galvanised iron, abrade with 240 grade paper to remove chemical treatments and allow full adhesion.</p> <p>CEMENT RENDER / MASONRY Allow masonry, cement render and mortar to cure for 28 days before painting.</p> <p>STEEL Remove rust and prime with a suitable Taubmans iron & steel primer or White Knight Rust Guard® Metal Primer.</p> <p>ZINCALUME® STEEL Wash with water and mild detergent. Surface must be clean and dry. Apply one coat of Taubmans 3 in 1 Prep.</p>
PREVIOUSLY PAINTED	Remove all loose and flaking paint. Apply Taubmans 3 in 1 Prep to aged enamel systems to provide intercoat adhesion.
AFTER PAINTING	Avoid exposure to steam for 48 hours. Surface may be washed after 7 days, but always avoid abrasive cleaners.
TEMPERATURE MIN	10 (°C)
TEMPERATURE MAX	35 (°C)
RECOATTEMPDEGREES	25 (°C)
RECOATHUMIDITYPERCENTAGE	50 (%)

APPLICATION

WET FILM THICKNESS	60 - 65 microns
DRY FILM THICKNESS	20 - 25 microns
STIRRING	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
BRUSH, ROLLER, SPRAY	Apply one or two coats (as per recommendation) by roller, brush or spray gun, with the recommended RECOAT time between each coat (refer to product spec). Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.
NAP ROLLER	10mm - 12mm Pile Roller
CURING	Avoid exposure to steam and condensation for 48 hours after painting.

DATASHEET

COVERAGE	Up to 16m ² /litre. Coverage on rough or absorbent surfaces will be lower.
APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS	10
APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS	35
COATS REQUIRED	One

PRECAUTIONS

GENERAL SAFETY INFORMATION

WALL PAINTS

SAFETY

Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

CEILING

SAFETY

Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

DANGER FLAMMABLE LIQUID AND VAPOUR

Warning. Flammable hydrocarbon liquid. Keep out of reach of children. Keep lid on when not in use.

Wear solvent resistant gloves and eye protection when using. Ensure adequate ventilation and do not breathe vapour.

FIRST AID INFORMATION

IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.

EYE CONTACT - Flush with plenty of water. Always seek medical advice.

SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.

INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.

AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686
Further information: www.taubmans.com.au

ENVIRONMENT INFORMATION

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au