

DATASHEET

# Taubmans Prep Right Quick Dry

# TAUBMANS

Product Code:  
111526



## Taubmans Prep Right Quick Dry

Taubmans Prep Right Quick Dry Undercoat seals and fills bare interior timber, metal and previously painted surfaces. For use especially with oil based topcoats.

### USES

Interior timber or primed metal surfaces. Suitable for both Interior and exterior use.

### FEATURES AND BENEFITS

<b>SCRUB RESISTANT</b>	Provides a tough and durable abrasion-resistant coating
<b>EASY TO APPLY</b>	Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.
<b>FAST DRYING</b>	Assist project completion timelines with fast drying properties
<b>AUSTRALIAN MADE</b>	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
<b>TINTABLE</b>	Tintable to over 10,000 colours. Order A4 samples or brush outs online at <a href="https://www.taubmans.com.au/specifiers/explore#search">https://www.taubmans.com.au/specifiers/explore#search</a>
<b>AUSTRALIAN STANDARD</b>	AS2311

### PRODUCT SPECIFICATIONS

<b>LOW SHEEN</b>	A subtle sheen level which is good for cleaning and hides surface imperfections better than gloss level paints. Ideal for all interior walls, all exterior walls, cement render / masonry, trim, roofs, timber, galvanised iron, PVC piping and steel
<b>VOC LEVELS</b>	459g/Litre
<b>DRY TIMES: TOUCH DRY</b>	30 mins
<b>DRY TIMES: RECOAT</b>	2 hours

## DATASHEET

<b>4L AVAILABLE SIZES</b>	4L
<b>SDS</b>	SDS available from the Taubmans Website <a href="http://taubmans.com.au">taubmans.com.au</a>
<b>EXTENSIVE COLOUR RANGE</b>	Tintable to over 10,000 colours. Order A4 samples or brush outs online at <a href="https://www.taubmans.com.au/specifiers/explore#search">https://www.taubmans.com.au/specifiers/explore#search</a>
<b>WHITE BASE</b>	Tint your desired colour from a White base

## SURFACE PREPARATION

<b>GENERAL INTERIOR</b>	Can include interior walls, ceilings, doors and architraves
<b>NEW WORK</b>	<p><b>TIMBER</b> Weathered (greyed) timber must be sanded to the original timber surface. Tannin rich timbers such as cedar should be primed with Taubmans 3 in 1 Prep or a suitable Taubmans oil based wood primer.</p> <p><b>GALVANISED IRON</b> Thoroughly degrease new surfaces. Weathered surfaces should be thoroughly cleaned before painting. For structural galvanised iron, abrade with 240 grade paper to remove chemical treatments and allow full adhesion.</p> <p><b>CEMENT RENDER / MASONRY</b> Allow masonry, cement render and mortar to cure for 28 days before painting.</p> <p><b>STEEL</b> Remove rust and prime with a suitable Taubmans iron &amp; steel primer or White Knight Rust Guard® Metal Primer.</p> <p><b>ZINCALUME® STEEL</b> Wash with water and mild detergent. Surface must be clean and dry. Apply one coat of Taubmans 3 in 1 Prep.</p>
<b>PREVIOUSLY PAINTED</b>	Remove all loose and flaking paint. Apply Taubmans 3 in 1 Prep to aged enamel systems to provide intercoat adhesion.
<b>AFTER PAINTING</b>	Avoid exposure to steam for 48 hours. Surface may be washed after 7 days, but always avoid abrasive cleaners.
<b>TEMPERATURE MIN</b>	10 (°C)
<b>TEMPERATURE MAX</b>	35 (°C)
<b>RECOATTEMPDEGREES</b>	25 (°C)
<b>RECOATHUMIDITYPERCENTAGE</b>	50 (%)

## APPLICATION

<b>WET FILM THICKNESS</b>	60 - 65 microns
<b>DRY FILM THICKNESS</b>	25 - 30 microns
<b>STIRRING</b>	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
<b>BRUSH, ROLLER, SPRAY</b>	Apply two coats by roller, brush or spray gun, with 2 hours between each coat. Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.

## DATASHEET

<b>NAP ROLLER</b>	10mm - 12mm Pile Roller
<b>CURING</b>	Avoid exposure to steam and condensation for 48 hours after painting.
<b>COVERAGE</b>	Up to 16 m <sup>2</sup> /litre.
<b>APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS</b>	10
<b>APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS</b>	30
<b>COATS REQUIRED</b>	One

## PRECAUTIONS

<b>GENERAL SAFETY INFORMATION</b>	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area. Do not store below 5 deg C temperature. Keep containers sealed when not in use
<b>DANGER FLAMMABLE LIQUID AND VAPOUR</b>	Warning. Flammable hydrocarbon liquid. Keep out of reach of children. Keep lid on when not in use. Wear solvent resistant gloves and eye protection when using. Ensure adequate ventilation and do not breathe vapour.
<b>FIRST AID INFORMATION</b>	IF SWALLOWED Do NOT induce vomiting. Seek medical advice immediately. EYE CONTACT Flush with plenty of water. Always seek medical advice. SKIN CONTACT Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water. INHALATION Remove to fresh air, seek medical advice if breathing is laboured. AUSTRALIA 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: <a href="http://www.taubmans.com.au">www.taubmans.com.au</a>
<b>ENVIRONMENT INFORMATION</b>	Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit <a href="http://paintback.com.au">paintback.com.au</a>

## ENVIRONMENT & SAFETY

<b>WARRANTY INFORMATION</b>	Taubmans paint that fails to give satisfactory results on properly prepared surfaces when applied according to printed directions, will be replaced.
-----------------------------	--

## DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

## CUSTOMER SERVICE/COMPANY CONTACT

## DATASHEET

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)