

DATASHEET

# Taubmans Tough Stain Blocker

# TAUBMANS

Product Code:  
111533



## Taubmans Tough Stain Blocker

Taubmans Tough Stain Blocker is a powerful oil based prep coat ideal for blocking a wide range of difficult stains. The fast drying formula has high hiding power and exceptional adhesion to a variety of tough to paint surfaces. The foundation for a superior finish.

## USES

Ideal for laminate, Perspex, PVC, polypropylene, varnish, aged enamels, timber, and previously painted surfaces.

## FEATURES AND BENEFITS

<b>AUSTRALIAN MADE</b>	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
<b>HIGH OPACITY</b>	Excellent hiding properties.
<b>FAST DRYING</b>	Assist project completion timelines with fast drying properties
<b>STAIN BLOCKER</b>	Excellent stain suppressing and sealing qualities. Effectively seals stains and provides a sound surface for top coats

## PRODUCT SPECIFICATIONS

<b>300GM AVAILABLE SIZES</b>	300gm
<b>1L AVAILABLE SIZES</b>	1L
<b>4L AVAILABLE SIZES</b>	4L
<b>SDS</b>	SDS available from the Taubmans Website <a href="http://taubmans.com.au">taubmans.com.au</a>
<b>CLEAN UP</b>	Mineral Turpentine
<b>GLOSS LEVEL</b>	<5 units (% at a 60 degree angle)

## DATASHEET

<b>WET FILM THICKNESS</b>	83µm
<b>DRY FILM THICKNESS</b>	35µm
<b>DRY TIMES: TOUCH DRY</b>	30 minutes
<b>DRY TIMES: RECOAT</b>	1 hour
<b>VOC LEVELS</b>	<500 g/L

## Surface Preparation

<b>TSB - PREPARATION</b>	<p>Surfaces must be clean, dry and free from all surface contamination. Fill in surface defects with suitable filler, putty or sealant. Remove stain as much as possible using a commercial cleaner or detergent and water. Rinse with water and allow to dry. For mould-based stains, use Taubmans Advanced Adhesion Mould Blocker.</p> <p>Always test stain blocking and adhesion on a small area prior to commencing project.</p>
--------------------------	--

## APPLICATION

<b>BRUSH OR ROLLER</b>	Apply one or two coats (as per recommendation) by brush or roller, with the recommended recoat time between each coat (refer to product spec). Paint corners and edges with a narrow brush. Roll up to the edges using a quality roller with the recommended nap (refer to product spec).
<b>COATS REQUIRED</b>	1
<b>NAP ROLLER</b>	12-16mm
<b>COVERAGE</b>	Up to 12m <sup>2</sup> /L
<b>STIRRING RECOMMENDATION</b>	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. Continue stirring at regular intervals during application.
<b>APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS</b>	10
<b>APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS</b>	35

## PRECAUTIONS

<b>DANGER FLAMMABLE LIQUID AND VAPOUR</b>	<p>Warning. Flammable hydrocarbon liquid. Keep out of reach of children. Keep lid on when not in use.</p> <p>Wear solvent resistant gloves and eye protection when using. Ensure adequate ventilation and do not breathe vapour.</p>
<b>GENERAL SAFETY INFORMATION</b>	<p>WALL PAINTS</p> <p>SAFETY</p> <p>Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p> <p>CEILING</p> <p>SAFETY</p>

## DATASHEET

Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

**FIRST AID INFORMATION**

IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.

EYE CONTACT - Flush with plenty of water. Always seek medical advice.

SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.

INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.

AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686  
Further information: [www.taubmans.com.au](http://www.taubmans.com.au)

**ENVIRONMENT INFORMATION**

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit [paintback.com.au](http://paintback.com.au)

**DISCLAIMER**

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

**CUSTOMER SERVICE/COMPANY CONTACT**

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)