

DATASHEET

Taubmans Prep Right Traditional Undercoat

TAUBMANS

Product Code:
111500



Taubmans Prep Right Traditional Undercoat

Taubmans Prep Right Oil Based Traditional Undercoat promotes outstanding adhesion over previously painted enamel surfaces. Oil Based Traditional Undercoat provides superior adhesion, enhances topcoat appearance for interior and exterior use.

USES

Both interior and suitably primed exterior surfaces.

FEATURES AND BENEFITS

MOULD RESISTANT	Helps prevent the growth of mould, mildew and fungus in damp areas
HIGH OPACITY	Excellent hiding properties.
EASY TO APPLY	Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.
INTERNAL AND EXTERNAL	Suitable for use in internal and external areas
AUSTRALIAN MADE	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
AUSTRALIAN STANDARD	AS2311, AS3730.14
APAS APPROVED	APAS 0016/1

PRODUCT SPECIFICATIONS

CLEAN UP	Mineral turps
GLOSS LEVEL	9-10 (% at a 60 degree angle)
VOC LEVELS	369g/Litre

DATASHEET

DRY TIMES: TOUCH DRY	4 hours
DRY TIMES: RECOAT	Recoat after 16 hours at 25°C and 50% relative humidity.
500ML AVAILABLE SIZES	500ml
1L AVAILABLE SIZES	1l
4L AVAILABLE SIZES	4l
10L AVAILABLE SIZES	10l
SDS	SDS available from the Taubmans Website taubmans.com.au
EXTENSIVE COLOUR RANGE	Tintable to over 10,000 colours. Order A4 samples or brush outs online at https://www.taubmans.com.au/specifiers/explore#search
WHITE BASE	Tint your desired colour from a White base

SURFACE PREPARATION

PREPARATION	Remove all loose and flaking paint. Remove surface chalk and powder, dirt, oil, rust and grease. Sand smooth before painting and sand lightly between coats. Surfaces must be clean and dry before painting. Prime bare metal and exterior timber surfaces in accordance with the specification for the surface to be painted as shown on the paint can label. For Example: Exterior timber - PrepRight Wood Primer. Galvanised steel, Aluminium, Zinalume - Taubmans 3 in 1. Steel - PrepRight Iron and Steel Primer.
AFTER PAINTING	Avoid exposure to steam for 48 hours. Surface may be washed after 7 days, but always avoid abrasive cleaners.
TEMPERATURE MIN	10 (°C)
TEMPERATURE MAX	35 (°C)
RECOATTEMPDEGREES	25 (°C)
RECOATHUMIDITYPERCENTAGE	50 (%)

APPLICATION

WET FILM THICKNESS	60 - 65 microns
DRY FILM THICKNESS	25 - 30 microns
STIRRING	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
BRUSH, ROLLER, SPRAY	Apply one or two coats (as per recommendation) by roller, brush or spray gun, with the recommended RECOAT time between each coat (refer to product spec). Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.
NAP ROLLER	10mm - 12mm Pile Roller
CURING	Avoid exposure to steam and condensation for 48 hours after painting.

DATASHEET

COVERAGE	Up to 16m ² /litre. Coverage will be lower on rough or absorbent surfaces.
APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS	10
APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS	35
COATS REQUIRED	One

PRECAUTIONS

GENERAL SAFETY INFORMATION	WALL PAINTS SAFETY	Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.
	CEILING SAFETY	Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.
DANGER FLAMMABLE LIQUID AND VAPOUR	Warning. Flammable hydrocarbon liquid. Keep out of reach of children. Keep lid on when not in use. Wear solvent resistant gloves and eye protection when using. Ensure adequate ventilation and do not breathe vapour.	
FIRST AID INFORMATION	IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately. EYE CONTACT - Flush with plenty of water. Always seek medical advice. SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water. INHALATION - Remove to fresh air, seek medical advice if breathing is laboured. AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au	
ENVIRONMENT INFORMATION	Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au	

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au