

DATASHEET

Taubmans Advanced Adhesion & Mould Blocker

TAUBMANS

Product Code:
111534



Taubmans Advanced Adhesion & Mould Blocker

Taubmans Advanced Adhesion & Mould Blocker is a specialised water based prepcoat, ideal for blocking persistent oil, grease, and mould-based stains and for inhibiting future mould growth. Perfect for high humidity areas, with exceptional adhesion to a range of challenging surfaces. The foundation for a superior finish.

USES

Interior & Exterior: Ideal for use on tiles, laminate, glass, perspex, PVC, varnish, aged enamels, masonry, timber, MDF, plywood, paperfaced plasterboard, bricks, cement sheet, galvanised steel, aluminium and previously painted surfaces.

FEATURES AND BENEFITS

APAS APPROVED	APAS 0172
AUSTRALIAN MADE	Our Aussie Heritage: Since our creation over a century ago in 1897 by George Henry Taubman, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success with our state-of-the-art plant in Clayton, VIC.
WATER BASED FORMULA	Easy clean up with water
STAIN BLOCKER	Excellent stain suppressing and sealing qualities. Effectively seals stains and provides a sound surface for top coats
MOULD RESISTANT	Helps prevent the growth of mould, mildew and fungus in damp areas
HIGH OPACITY	Excellent hiding properties.
EXCELLENT ADHESION	Provides excellent adhesion to difficult surfaces.
INTERNAL AND EXTERNAL	Suitable for use in internal and external areas

PRODUCT SPECIFICATIONS

4L AVAILABLE SIZES	4L
---------------------------	----

DATASHEET

1L AVAILABLE SIZES	1L
500ML AVAILABLE SIZES	500ml
SDS	SDS available at www.ppgmsds.com.au
CLEAN UP	Water
GLOSS LEVEL	<5 units (% at a 60 degree angle)
DRY FILM THICKNESS	24µm
DRY TIMES: RECOAT	2 hours
DRY TIMES: TOUCH DRY	30 minutes
WET FILM THICKNESS	72µm
VOC LEVELS	<30g/L
WHITE BASE	Do not tint

Surface Preparation

ADHESION AND MOULD - PREPARATION

Surfaces must be clean, dry and free from all surface contamination. Fill in surface defects with suitable filler, putty or sealant. Treat mould with bleach or Flood Mould Action and then rinse with clean water. Taubmans Advanced Adhesion Mould Blocker is designed to seal light mould stains and inhibit future growth. Untreated heavy mould growth will continue. Remove stain as much as possible using a commercial cleaner or detergent and water. Rinse with water and allow to dry. For water-based stains, use Taubmans Tough Stain Blocker.

Always test stain blocking and adhesion on a small area prior to commencing project.

APPLICATION

COATS REQUIRED	One
CURING	Avoid exposure to steam and condensation for 48 hours after painting.
NAP ROLLER	12-16mm
COVERAGE	Up to 14m ² /L
STIRRING RECOMMENDATION	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. Continue stirring at regular intervals during application
APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS	10
APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS	35
BRUSH OR ROLLER	Apply one or two coats (as per recommendation) by brush or roller, with the recommended recoat time between each coat (refer to product spec). Paint corners and edges with a narrow brush. Roll up to the edges using a quality roller with the recommended nap (refer to product spec).

DATASHEET

PRECAUTIONS

GENERAL SAFETY INFORMATION

WALL PAINTS

SAFETY

Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes; wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

CEILING

SAFETY

Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

FIRST AID INFORMATION

IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.

EYE CONTACT - Flush with plenty of water. Always seek medical advice.

SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.

INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.

AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au

ENVIRONMENT INFORMATION

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

VERSION

VERSION NUMBER

1.2

VERSION DATE

29 July 2024

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au