

DATASHEET

Taubmans Armawall Villa Sands

TAUBMANS

Product Code:
305034



Taubmans Armawall Villa Sands

Taubmans Armawall Villa Sands is a tough, acrylic texture coating that produces a render-like effect. Can be applied to achieve a smooth finish on rough or uneven surfaces. Gives a medium grade granular texture when applied with a trowel and finished with a plastic float. Excellent weatherproofing and impact resistance. Armawall Villa Sands can be sprayed through a hopper gun or texture spray unit, giving a stucco style finish. Topcoat with Armawall Armashield, Armawall Roll On Membrane or Armawall Satin for enhanced durability and substrate protection.

USES

Exterior cement render, masonry, fibrous cement sheeting, AAC panels and blocks, bricks and blockwork.

FEATURES AND BENEFITS

DURABILITY	Excellent weatherproofing and impact resistance
FINISH	Matt Finish – Contemporary finish that minimises surface imperfections
STABLE BASE	Can be applied as a single tinted coat over Armawall Primer (see Application)
WEATHER RESISTANCE	Provides advanced protection against the extremes of weather
FLEXIBLE	Withstands normal substrate movements
VAPOR PERMEABILITY	Allows substrate to breathe to reduce moisture entrapment
AUSTRALIAN MADE	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
WATER BASED FORMULA	Easy clean up with water

PRODUCT SPECIFICATIONS

DATASHEET

ABRASION RESISTANCE	Good
WATER RESISTANT	Excellent
COLOUR RANGE	Available in a wide range of colours
PROFILE	Low and High
CLEAN UP	Water away from drains and watercourses
VOLUME SOLIDS (%)	62.7
VOC LEVELS	<50g/Litre
DRY TIMES: TOUCH DRY	60 mins
DRY TIMES: RECOAT	24 hours (Note: This may be lengthened in damp, cold or humid conditions. Do not apply at temperatures below 10°C)
15L AVAILABLE SIZES	15L
SDS	SDS available from the Taubmans Website taubmans.com.au

Surface Preparation

NEW CEMENT RENDER MASONRY & CONCRETE (ARMAWALL)

New cement render, masonry and concrete surfaces should be allowed to cure for 28 days. Off form concrete should be thoroughly cleaned by acid etching, water or sand blasting to ensure all bond breaker oils are removed. Aged concrete masonry and fibro surfaces in sound condition should be scrubbed down with detergent and fresh water, fresh water washed and allowed to dry. Surface irregularities such as blow holes and profile defects may require patching with Armawall Smooth Patch or Armawall Coarse Patch prior to system application.

SURFACE PREPARATION

SUBSTRATE MOISTURE CONTENT (ARMAWALL)

Moisture content of the substrate must be no greater than 15% wood-moisture-equivalent (WME) prior to or during application, to ensure optimal coating system performance

APPLICATION

ODOUR	Low
WET FILM THICKNESS	1-3 mm
DRY FILM THICKNESS	1-3 mm
STIRRING	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
NAP ROLLER	Steel Trowel

DATASHEET

STAINLESS STEEL TROWEL, RED PLASTIC FLOAT

Working in an upward action with the trowel, hold trowel & material against wall and evenly apply material. Now working in a tight circular motion with the RED PLASTIC FLOAT, Run the float over the surface, remember to keep the float FLAT on the wall to ensure even & smooth back the texture. Remember that the RED PLASTIC FLOAT will act as a razor and shave off any high areas of material. This can lead to some material wastage if the material is applied to thickly.

STAINLESS STEEL TROWEL, TEXTURE SPRAY, ROLLER

Yes

COVERAGE

1m²/litre at 1mm film thickness

APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS

10

APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS

35

COATS REQUIRED

One or two

PRECAUTIONS

GENERAL SAFETY INFORMATION

WALL PAINTS

SAFETY

Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

CEILING

SAFETY

Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

FIRST AID INFORMATION

IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.

EYE CONTACT - Flush with plenty of water. Always seek medical advice.

SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.

INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.

AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686
Further information: www.taubmans.com.au

ENVIRONMENT INFORMATION

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au