

DATASHEET

Taubmans All Weather® Exterior Matt

TAUBMANS

Product Code:
187100



Taubmans All Weather® Exterior Matt

Taubmans All Weather Exterior Matt offers superior performance against leading competitors, making it the perfect choice for exterior surfaces. Engineered with Nanoguard® Advanced Technology, it has an interlocking molecular structure that works to create a protective shield, so dirt can be washed away without compromising the quality of the paint or damaging the finish. It comes with a lifetime guarantee* against peeling, flaking, and blistering. Taubmans All Weather is a self-priming water based paint that has as a total UV blockout to protect the coating and substrate against the sun.



USES

Exterior surfaces recommended include cement render, masonry, PVC piping, galvanised iron, steel, timber, and roofs.

FEATURES AND BENEFITS

ADVANCED NANOGUARD® TECHNOLOGY	Contains an interlocking molecular structure that creates a protective shield, so everyday dirt and stains can be wiped away without compromising the quality of the paint. It provides excellent mould and mildew protection - so you have a cleaner and healthier home environment
SCRUB RESISTANT	Provides a tough and durable abrasion-resistant coating
ADVANCED WASHABILITY	Resists burnishing – the formation of shiny patches on washing.
MOULD RESISTANT	Prevents the growth of mould, mildew and fungus in damp areas
HIGH OPACITY	Excellent hiding properties.
EASY TO APPLY	Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.
ALL WEATHER PROTECTION	Built with advanced UV protection technology to resists cracking & peeling from harsh weather conditions longer
FLEXIBLE	Withstands normal substrate movements
FLAT FINISH	Gives a flat finish with excellent surface defect hiding properties.

DATASHEET

FAST DRYING	Assist project completion timelines with fast drying properties
DIRT SHEDDING FORMULA	Protects surfaces and keeps them looking newer for longer by easily washing away dirt and pollutants from the surface
SELF-PRIMING	In most cases, removes the need for a prep coat
AUSTRALIAN MADE	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
TINTABLE	Tintable to over 10,000 colours. Order A4 samples or brush outs online at https://www.taubmans.com.au/specifiers/explore#search
AUSTRALIAN STANDARD	AS3730.8
ADVANCED FLOW MODIFIERS	Promotes ease of application, good flow properties and minimal roller splatter
APAS NUMBER	APAS 0280/3
ACRYLIC BINDER	Superior adhesion, flexibility, gloss retention & durability
UV PROTECTION	Blocks out harmful UV rays for longer lasting results
WATER BASED FORMULA	Easy clean up with water

PRODUCT SPECIFICATIONS

MATT	<p>Can be applied to uneven surfaces in order to hide imperfections.</p> <p>May mark more easily than high sheen products, so is therefore not recommended for high traffic areas.</p> <p>Ideal for interior walls; an ultra-washable, stain resistant matt finish.</p> <p>Ideal for exterior walls, cement render / masonry, trim, timber, galvanised iron, PVC piping and steel. Not suitable for surfaces used to collect drinking water</p>
GLOSS LEVEL	3-5 (% at a 60 degree angle)
VOC LEVELS	35g/Litre. Meets Green Building Council Requirements
DRY TIMES: TOUCH DRY	30 mins
DRY TIMES: RECOAT	2 hours
1L AVAILABLE SIZES	1l
4L AVAILABLE SIZES	4l
10L AVAILABLE SIZES	10l
15L AVAILABLE SIZES	15l
SDS	SDS available from the Taubmans Website taubmans.com.au
EXTENSIVE COLOUR RANGE	Tintable to over 10,000 colours. Order A4 samples or brush outs online at https://www.taubmans.com.au/specifiers/explore#search

DATASHEET

WHITE BASE	Tint your desired colour from a White base
ACCENT BASE	Tint your desired colour from an Accent base
NEUTRAL BASE	Tint your desired colour from a Neutral base

SURFACE PREPARATION

GENERAL EXTERIOR	Can include exterior walls, cement render / masonry, trim, timber, galvanised iron, PVC piping and steel
NEW WORK	<p>TIMBER</p> <p>Weathered (greyed) timber must be sanded to the original timber surface. Tannin rich timbers such as cedar may require two coats or use Taubmans Oil Based Wood Primer.</p> <p>GALVANISED IRON</p> <p>Thoroughly degrease new surfaces. Weathered surfaces should be thoroughly cleaned before painting. For structural galvanised iron, abrade with Z40 grade paper to remove chemical treatments and allow full adhesion.</p> <p>CEMENT RENDER / MASONRY</p> <p>Allow masonry, cement render and mortar to cure for 28 days before painting.</p> <p>STEEL</p> <p>Remove rust and prime with a suitable Taubmans iron & steel primer or White Knight Rust Guard® Metal Primer.</p> <p>ZINCALUME® STEEL</p> <p>Wash with water and mild detergent. Surface must be clean and dry. Apply one coat of Taubmans 3 in 1 Prep.</p>
PREVIOUSLY PAINTED	Remove all loose and flaking paint. Apply Taubmans 3 in 1 Prep to aged enamel systems to provide intercoat adhesion.
TEMPERATURE MIN	10 (°C)
TEMPERATURE MAX	35 (°C)
RECOATTEMPDEGREES	25 (°C)
RECOATHUMIDITYPERCENTAGE	50 (%)

APPLICATION

WET FILM THICKNESS	60 - 65 microns
DRY FILM THICKNESS	25 - 30 microns
STIRRING	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
BRUSH, ROLLER, SPRAY	Apply 1 or 2 coats (as per recommendation) by roller, brush or spray gun, with 2 hours between each coat. Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.
NAP ROLLER	10mm - 12mm Pile Roller

DATASHEET

COVERAGE	16m ² /litre.
APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS	10
APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS	35
COATS REQUIRED	Two minimum

PRECAUTIONS

GENERAL SAFETY INFORMATION	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area. Do not store below 5 deg C temperature. Keep containers sealed when not in use
FIRST AID INFORMATION	IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately. EYE CONTACT - Flush with plenty of water. Always seek medical advice. SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water. INHALATION - Remove to fresh air, seek medical advice if breathing is laboured. AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au
ENVIRONMENT INFORMATION	Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

ENVIRONMENT & SAFETY

WARRANTY INFORMATION	Taubmans All Weather Exterior are guaranteed against blistering, flaking or peeling if applied on suitable and properly prepared surfaces according to printed directions. This guarantee applies to the owner of the house/property to which the paint has been applied for the duration that the owner owns the house/property to which the paint has been applied. The benefits provided under this guarantee are personal and are not transferable. This guarantee is given by PPG Industries Australia Pty Ltd. This guarantee applies to defects in the manufacture or formulation of the paint and does not cover paint failure caused by factors beyond our control. If this guarantee is not met, we will replace the paint or refund your money. We are not liable for the cost of labour or any other direct or indirect loss or damage arising from a breach of this guarantee. Customers are responsible for all costs of claiming under this guarantee. To claim, customers must write to us or call our Customer Care number to request a claim form. The benefits provided by this guarantee are in addition to other rights and remedies under the law. If you are a consumer within the meaning of the Australian Consumer Law: Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.
-----------------------------	--

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au