

DATASHEET

Taubmans Professional Water Based Gloss Enamel

TAUBMANS

Product Code:
278600



Taubmans Professional Water Based Gloss Enamel

Taubmans Professional Water Based Enamel is a high-quality, easy-to-apply, and quick-drying formula specially designed to protect doors, trims, skirting boards, and windows.

USES

Ideal for all interior and exterior doors and trims

FEATURES AND BENEFITS

SCRUB RESISTANT	Provides a tough and durable abrasion-resistant coating
ADVANCED WASHABILITY	Resists burnishing – the formation of shiny patches on washing.
LOW VOC	Contains low level of VOC to conform to requirements of Green Building Council of Australia (GBCA).
MOULD RESISTANT	Helps prevent the growth of mould, mildew and fungus in damp areas
HIGH OPACITY	Excellent hiding properties.
EASY TO APPLY	Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.
NON YELLOWING FORMULA	Technologically advanced non-yellowing formula
ALL WEATHER PROTECTION	Built with advanced UV protection technology to resists cracking & peeling from harsh weather conditions longer
INTERNAL AND EXTERNAL	Suitable for use in internal and external areas
FLEXIBLE	Withstands normal substrate movements
FAST DRYING	Assist project completion timelines with fast drying properties
AUSTRALIAN MADE	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.

DATASHEET

ADVANCED FLOW MODIFIERS	Promotes ease of application, good flow properties and minimal roller splatter
ACRYLIC BINDER	Superior adhesion, flexibility, gloss retention & durability
WATER BASED FORMULA	Easy clean up with water

PRODUCT SPECIFICATIONS

GLOSS LEVEL	75-80 at 60° (% at a 60 degree angle)
VOC LEVELS	75g/Litre
DRY TIMES: TOUCH DRY	30 mins
DRY TIMES: RECOAT	2 hours
4L AVAILABLE SIZES	4l
10L AVAILABLE SIZES	10l
SDS	SDS available from the Taubmans Website taubmans.com.au
WHITE BASE	Tint your desired colour from a White base

SURFACE PREPARATION

NEW/BAREWORK	Paper faced plasterboard, masonry and timber - apply one coat of Taubmans 3 in 1 Prep. Surfaces must be clean, dry and free from all surface contamination. Treat mould with bleach then rinse with clean water. Fill in the surface defects with suitable filler, putty or sealant.
PREVIOUSLY PAINTED	Remove all loose and flaking paint. Apply Taubmans 3 in 1 Prep to aged enamel systems to provide intercoat adhesion.
AFTER PAINTING	Avoid exposure to steam for 48 hours. Surface may be washed after 7 days, but always avoid abrasive cleaners.
TEMPERATURE MIN	10 (°C)
TEMPERATURE MAX	35 (°C)
RECOATTEMPDEGREES	25 (°C)
RECOATHUMIDITYPERCENTAGE	50 (%)

APPLICATION

WET FILM THICKNESS	60 -65 microns
DRY FILM THICKNESS	25 - 30 microns

DATASHEET

STIRRING	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
NAP ROLLER	Apply two coats using a 4mm - 6mm (length of nap or pile) roller, good quality brush or spray. Avoid overspreading. If painting a large flat trim area, such as a door, apply by roller for best appearance.
CURING	Avoid exposure to steam and condensation for 48 hours after painting.
COVERAGE	Up to 16m ² per litre. Coverage will be lower on rough or absorbent surfaces.
APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS	10
APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS	35
COATS REQUIRED	2

PRECAUTIONS

GENERAL SAFETY INFORMATION	WALL PAINTS SAFETY	Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.
	CEILING SAFETY	Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.
FIRST AID INFORMATION	IF SWALLOWED	- Do NOT induce vomiting. Seek medical advice immediately.
	EYE CONTACT	- Flush with plenty of water. Always seek medical advice.
	SKIN CONTACT	- Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.
	INHALATION	- Remove to fresh air, seek medical advice if breathing is laboured.
	AUSTRALIA	- 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au
ENVIRONMENT INFORMATION		Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au