

DATASHEET

Taubmans Ultimate Enamel Low Sheen

TAUBMANS

Product Code:
132210



Taubmans Ultimate Enamel Low Sheen

Taubmans® Ultimate Enamel is a premium, fast drying enamel that uses superior alkyd technology to provide the durability and performance of a traditional oil based enamel, while also being environmentally friendly because it's water based. This innovative technology provides faster dry times and less yellowing than a traditional oil based enamel, while maintaining a smooth finish. Taubmans Ultimate Enamel inhibits mould and mildew, has low VOC, less odour and an easy water clean up. Ultimate Enamel is the ideal choice for a high end professional finish.



USES

Suitable for all interior and sheltered exterior doors, trims and windows.

FEATURES AND BENEFITS

| | |
|------------------------------|---|
| SCRUB RESISTANT | Provides a tough and durable abrasion-resistant coating |
| LOW VOC | Contains low level of VOC to conform to requirements of Green Building Council of Australia (GBCA). |
| MOULD RESISTANT | Prevents the growth of mould, mildew and fungus in damp areas |
| HIGH OPACITY | Excellent hiding properties. |
| EASY TO APPLY | Holds a wet edge longer to minimise lap marks and create a smooth uniform finish. |
| INTERNAL AND EXTERNAL | Suitable for use in internal and external areas |
| FLEXIBLE | Withstands normal substrate movements |
| FAST DRYING | Assist project completion timelines with fast drying properties |
| AUSTRALIAN MADE | Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC. |

DATASHEET

| | |
|--------------------------------|---|
| TINTABLE | Tintable to over 10,000 colours. Order A4 samples or brush outs online at https://www.taubmans.com.au/specifiers/explore#search |
| AUSTRALIAN STANDARD | AS2311 |
| ADVANCED FLOW MODIFIERS | Promotes ease of application, good flow properties and minimal roller splatter |
| WATER BASED FORMULA | Easy clean up with water |

PRODUCT SPECIFICATIONS

| | |
|-------------------------------|--|
| LOW SHEEN | A subtle sheen level which is good for cleaning and hides surface imperfections better than gloss level paints. Ideal for all interior walls, all exterior walls, cement render / masonry, trim, roofs, timber, galvanised iron, PVC piping and steel |
| VOC LEVELS | 35g/Litre |
| DRY TIMES: TOUCH DRY | 4-6 hours |
| DRY TIMES: RECOAT | 24 hours |
| 1L AVAILABLE SIZES | 1L |
| 4L AVAILABLE SIZES | 4L |
| 10L AVAILABLE SIZES | 10L |
| SDS | SDS available from the Taubmans Website taubmans.com.au |
| EXTENSIVE COLOUR RANGE | Tintable to over 10,000 colours. Order A4 samples or brush outs online at https://www.taubmans.com.au/specifiers/explore#search |
| WHITE BASE | Tint your desired colour from a White base |
| ACCENT BASE | Tint your desired colour from an Accent base |
| NEUTRAL BASE | Tint your desired colour from a Neutral base |

SURFACE PREPARATION

| | |
|-------------------------|--|
| GENERAL INTERIOR | Can include interior walls, ceilings, doors and architraves |
| GENERAL EXTERIOR | Can include exterior walls, cement render / masonry, trim, timber, galvanised iron, PVC piping and steel |
| NEW WORK | <p>TIMBER</p> <p>Weathered (greyed) timber must be sanded to the original timber surface. Tannin rich timbers such as cedar may require two coats or use Taubmans Oil Based Wood Primer.</p> <p>GALVANISED IRON</p> <p>Thoroughly degrease new surfaces. Weathered surfaces should be thoroughly cleaned before painting. For structural galvanised iron, abrade with 240 grade paper to remove chemical treatments and allow full adhesion.</p> |

DATASHEET

CEMENT RENDER / MASONRY

Allow masonry, cement render and mortar to cure for 28 days before painting.

STEEL

Remove rust and prime with a suitable Taubmans iron & steel primer or White Knight Rust Guard® Metal Primer.

ZINCALUME® STEEL

Wash with water and mild detergent. Surface must be clean and dry. Apply one coat of Taubmans 3 in 1 Prep.

| | |
|---------------------------------|--|
| PREVIOUSLY PAINTED | Remove all loose and flaking paint. Apply Taubmans 3 in 1 Prep to aged enamel systems to provide intercoat adhesion. |
| AFTER PAINTING | Avoid exposure to steam for 48 hours. Surface may be washed after 7 days, but always avoid abrasive cleaners. |
| TEMPERATURE MIN | 10 (°C) |
| TEMPERATURE MAX | 35 (°C) |
| RECOATTEMPDEGREES | 25 (°C) |
| RECOATHUMIDITYPERCENTAGE | 50 (%) |

APPLICATION

| | |
|--|---|
| WET FILM THICKNESS | 60-65 microns |
| DRY FILM THICKNESS | 25-50 microns |
| STIRRING | Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency |
| BRUSH, ROLLER, SPRAY | Apply 1 or 2 coats (as per recommendation) by roller, brush or spray gun, with 2 hours between each coat. Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller. |
| NAP ROLLER | 5mm Pile Roller |
| CURING | Avoid exposure to steam and condensation for 48 hours after painting. |
| COVERAGE | Up to 16sqm/litre. |
| APPLICATION TEMPERATURE MINIMUM DEGREES CELSIUS | 10 |
| APPLICATION TEMPERATURE MAXIMUM DEGREES CELSIUS | 35 |
| COATS REQUIRED | Two |

PRECAUTIONS

| | |
|-----------------------------------|--|
| GENERAL SAFETY INFORMATION | Store in original container protected from direct sunlight in a dry, cool and well-ventilated area. Do not store below 5 deg C temperature. Keep containers sealed when not in use |
| FIRST AID INFORMATION | IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately. EYE CONTACT - Flush with plenty of water. Always seek medical advice. |

DATASHEET

SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.
INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.

AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686
Further information: www.taubmans.com.au

**ENVIRONMENT
INFORMATION**

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

ENVIRONMENT & SAFETY**WARRANTY INFORMATION**

The Australian Paint Manufacturers' Federation has issued the following general warning to assist specifiers and end users understanding one of the key characteristics of oil based paint. All white and pale coloured enamels will yellow with age. These enamels will yellow more rapidly in areas of low natural light, when applied in poorly ventilated conditions, or in the presence of ammonia - common in water based paints and some household chemicals. Only the use of water based acrylics can assure resistance to yellowing.

**LOW VOLATILE ORGANIC
COMPOUND**

Helps to improve indoor air quality

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au