

DATASHEET

Taubmans Trade Pro Undercoat

TAUBMANS

Product Code:
236500



Taubmans Trade Pro Undercoat

The Taubmans Trade Pro range is a water based paint designed specifically for the trade painter. The range extends Precoats, Walls & Ceiling. Easy to apply, it also provides good coverage for all your interior painting needs.

USES

Precoat for interior surfaces

FEATURES AND BENEFITS

EASY TO APPLY	Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.
NON YELLOWING FORMULA	Technologically advanced non-yellowing formula
FLAT FINISH	Gives a flat finish with excellent surface defect hiding properties.
FAST DRYING	Assist project completion timelines with fast drying properties
AUSTRALIAN MADE	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
TINTABLE	Tintable to over 10,000 colours. Order A4 samples or brush outs online at https://www.taubmans.com.au/specifiers/explore#search
AUSTRALIAN STANDARD	AS2311
ADVANCED FLOW MODIFIERS	Promotes ease of application, good flow properties and minimal roller splatter
ACRYLIC BINDER	Superior adhesion, flexibility, gloss retention & durability
WATER BASED FORMULA	Easy clean up with water

PRODUCT SPECIFICATIONS

DATASHEET

FLAT	Designed to produce flat uniform finish with no roller marks
GLOSS LEVEL	1-2 at 60° (% at a 60 degree angle)
VOC LEVELS	31g/Litre
DRY TIMES: TOUCH DRY	30 mins
DRY TIMES: RECOAT	2 hours
4L AVAILABLE SIZES	4l
10L AVAILABLE SIZES	10l
15L AVAILABLE SIZES	15l
SDS	SDS available from the Taubmans Website taubmans.com.au
EXTENSIVE COLOUR RANGE	Tintable to over 10,000 colours. Order A4 samples or brush outs online at https://www.taubmans.com.au/specifiers/explore#search
WHITE BASE	Tint your desired colour from a White base

SURFACE PREPARATION

GENERAL INTERIOR	Can include interior walls, ceilings, doors and architraves
NEW WORK	<p>TIMBER Weathered (greyed) timber must be sanded to the original timber surface. Tannin rich timbers such as cedar should be primed with Taubmans 3 in 1 Prep or a suitable Taubmans oil based wood primer.</p> <p>GALVANISED IRON Thoroughly degrease new surfaces. Weathered surfaces should be thoroughly cleaned before painting. For structural galvanised iron, abrade with 240 grade paper to remove chemical treatments and allow full adhesion.</p> <p>CEMENT RENDER / MASONRY Allow masonry, cement render and mortar to cure for 28 days before painting.</p> <p>STEEL Remove rust and prime with a suitable Taubmans iron & steel primer or White Knight Rust Guard® Metal Primer.</p> <p>ZINCALUME® STEEL Wash with water and mild detergent. Surface must be clean and dry. Apply one coat of Taubmans 3 in 1 Prep.</p>
PREVIOUSLY PAINTED	Remove all loose and flaking paint. Apply Taubmans 3 in 1 Prep to aged enamel systems to provide intercoat adhesion.
AFTER PAINTING	Avoid exposure to steam for 48 hours. Surface may be washed after 7 days, but always avoid abrasive cleaners.
TEMPERATURE MIN	10 (°C)
TEMPERATURE MAX	35 (°C)
RECOATTEMPDEGREES	25 (°C)

DATASHEET

RECOATHUMIDITYPERCENTAGE 50 (%)

APPLICATION

WET FILM THICKNESS 60 - 65 microns

DRY FILM THICKNESS 25 - 30 microns

STIRRING Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency

BRUSH, ROLLER, SPRAY Apply two coats by roller, brush or spray gun, with 2 hours between each coat. Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.

NAP ROLLER 10mm - 12mm Pile Roller

COVERAGE 16m²/litre.

MAINTENANCE - DECKING No

**APPLICATION TEMPERATURE
MINIMUM DEGREES CELCIUS** 10

**APPLICATION TEMPERATURE
MAXIMUM DEGREES CELCIUS** 35

COATS REQUIRED One

PRECAUTIONS

GENERAL SAFETY INFORMATION Store in original container protected from direct sunlight in a dry, cool and well-ventilated area. Do not store below 5 deg C temperature. Keep containers sealed when not in use

FIRST AID INFORMATION

IF SWALLOWED
Do NOT induce vomiting. Seek medical advice immediately.

EYE CONTACT
Flush with plenty of water. Always seek medical advice.

SKIN CONTACT
Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.

INHALATION
Remove to fresh air, seek medical advice if breathing is laboured.

AUSTRALIA
24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au

ENVIRONMENT INFORMATION Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

DISCLAIMER

DATASHEET

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au