

DATASHEET

Taubmans Armawall Roll on Render

TAUBMANS

Product Code:
315023



Taubmans Armawall Roll on Render

Taubmans Armawall Roll on Render is a thin section pre-mixed acrylic render, or patching compound, that produces a smooth render effect. Armawall Roll on Render is an innovative product which challenges the traditional method of applying a render style finish. Armawall Roll on Render is designed for a roll on, trowelled off application but is also suitable for conventional rendering methods.

USES

Recommended for creating a smooth render effect on cement block, AAC Hebel, cement render, fibre cement and previously painted surfaces.

FEATURES AND BENEFITS

CEMENT FREE	User friendly
FINISH	Suitable for topcoating with low profile texture finishes such as Armawall Ultrafine Flat, Armawall Armashield, Armawall Impact and Armawall Roll On Membrane
PRE-MIXED ACRYLIC RENDER	Resists cracking, crazing and drummy render issues associated with traditional sand & cement renders.
VAPOR PERMEABILITY	Allows substrate to breathe to reduce moisture entrapment
AUSTRALIAN MADE	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
WATER BASED FORMULA	Easy clean up with water

PRODUCT SPECIFICATIONS

COLOUR RANGE	Off white. May be coloured with machine colourants.
SPREAD RATE	1m ² /litre at 1mm dry film thickness
PROFILE	Smooth render finish

DATASHEET

VOC LEVELS	31g/Litre
DRY TIMES: TOUCH DRY	60 mins
DRY TIMES: RECOAT	48 hours
15L AVAILABLE SIZES	15L
SDS	SDS available from the Taubmans Website taubmans.com.au

Surface Preparation

GENERAL-ARMAWALL	Surface preparation is the responsibility of the Applicator, Builder, Renovator or Main Contractor. Armawall Surface Preparation Products are designed to perform at their optimum when used as part of an Armawall Texture Coating System.
NEW CEMENT RENDER MASONRY & CONCRETE (ARMAWALL)	New cement render, masonry and concrete surfaces should be allowed to cure for 28 days. Off form concrete should be thoroughly cleaned by acid etching, water or sand blasting to ensure all bond breaker oils are removed. Aged concrete masonry and fibro surfaces in sound condition should be scrubbed down with detergent and fresh water, fresh water washed and allowed to dry. Surface irregularities such as blow holes and profile defects may require patching with Armawall Smooth Patch or Armawall Coarse Patch prior to system application.

SURFACE PREPARATION

ACRYLIC PAINTED SURFACES	Confirm that the existing coating is sound by x-cut and tape adhesion test. Surfaces to be rendered must be clean and dry.
AGED ENAMEL	Surfaces to be rendered must be clean and dry. Confirm that the existing coating is sound by x-cut and tape adhesion test. Apply one coat of Taubmans Tradex Tradecoat.
CEMENT SHEETING RECESSED EDGE	Surfaces to be rendered must be clean and dry. Fibre Cement Sheeting must be installed strictly in accordance with the manufacturer's written instructions. The jointing system, which must be used is: 1. Apply a little Armawall Patch Coarse (mixed with 20% cement. Refer Data Sheet (223(B), embed Armawall Mesh (Fibreglass Tape) into the joint. Apply a second coat little Armawall Patch Coarse (mixed with 20% cement. Refer Data Sheet (223(B) to level the recess and to the sheet face. Allow to dry for minimum 24 hours. When fixing perforated angle bead to external / internal corners fit using the same process, over lapping the Armawall Mesh ½ to the angle and ½ to the sheet. Skim the entire length with the same Armawall Coarse Patch compound.
SUBSTRATE MOISTURE CONTENT	Moisture content of the substrate must be no greater than 15% wood-moisture-equivalent (WME) prior to or during application, to ensure optimal coating system performance
PREVIOUSLY PAINTED	Remove all loose and flaking paint. Apply Taubmans 3 in 1 Prep to aged enamel systems to provide intercoat adhesion.
TEMPERATURE MIN	10 (°C)
TEMPERATURE MAX	35 (°C)
RECOATTEMPDEGREES	25 (°C)
RECOATHUMIDITYPERCENTAGE	50 (%)

APPLICATION

FINISHING	This product is a surface preparation product only, as such it should be used in conjunction with the complete Armawall Texture System and specification. As a surface preparation product it should not be left exposed for
------------------	--

DATASHEET

more than 4 weeks of curing. The finishing system should be applied in a continual time frame, please refer to the Armawall Product Data Sheet for drying times.

APPLICATION	Apply with loop texture roller, then back trowel to an even sand finish with a plastic trowel. If the roller slips, apply a thin coat of Armawall Ultrafine or similar to provide grip.
STIRRING RECOMMENDATION	Stir until uniform, preferably with a mechanical stirrer
TROWEL ON	APPLY WITH TROWEL
WET FILM THICKNESS	1-3 mm
DRY FILM THICKNESS	1-2 mm
STIRRING	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
NAP ROLLER	16mm Pile Roller
STAINLESS STEEL TROWEL, RED PLASTIC FLOAT	Working in an upward action with the trowel, hold trowel & material against wall and evenly apply material. Now working in a tight circular motion with the RED PLASTIC FLOAT, Run the float over the surface, remember to keep the float FLAT on the wall to ensure even & smooth back the texture. Remember that the RED PLASTIC FLOAT will act as a razor and shave off any high areas of material. This can lead to some material wastage if the material is applied to thickly.
COVERAGE	1 m2/litre
APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS	10
APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS	35
COATS REQUIRED	One or Two

PRECAUTIONS

GENERAL SAFETY INFORMATION	<p>WALL PAINTS</p> <p>SAFETY</p> <p>Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p> <p>CEILING</p> <p>SAFETY</p> <p>Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p>
FIRST AID INFORMATION	<p>IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.</p> <p>EYE CONTACT - Flush with plenty of water. Always seek medical advice.</p> <p>SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.</p> <p>INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.</p> <p>AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au</p>

DATASHEET

ENVIRONMENT INFORMATION

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au