

DATASHEET

Taubmans Armawall Render Coarse

TAUBMANS

Product Code:
30008906



Taubmans Armawall Render Coarse

Taubmans Armawall Render Coarse is a pre-blended polymer modified cement render, and can be applied with ease, screeded and finished with an approved Taubmans Armawall Texture System. It only requires the addition of clean water and mixing before application. Taubmans Armawall Render Coarse is an exterior render, to be used over suitably prepared common masonry substrates - AAC, AFS, brickwork, concrete and polystyrene. Taubmans Armawall Render Coarse is suitable for traditional hawk and trowel hand application. Mix on site immediately before application. Taubmans Armawall Render Coarse must not be applied over previously painted surfaces.

USES

Exterior & Interior rendering applications, to be used as a cement based render over all common building substrates. Particularly suited for application onto AAC panel and blocks, conventional brick and block work. Do not apply to fibre cement sheeting, cladding or previously painted surfaces.

Recommended for AAC & other Masonry Substrates

FEATURES AND BENEFITS

NON COMBUSTIBLE CERTIFIED	The specimens are deemed NOT COMBUSTIBLE according to the test criteria specified in Clause 3.4 of AS 1530.1-1994. Please note, additions to the render not specified in this datasheet may void the non-combustibility rating of this product.
PRE-MIXED ACRYLIC RENDER	Resists cracking, crazing and drummy render issues associated with traditional sand & cement renders.
AUSTRALIAN MADE	Our Aussie Heritage: Since our creation over a century ago in 1897 by George Henry Taubman, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success with our state-of-the-art plant in Clayton, VIC.
ACRYLIC BINDER (ARMAWALL)	Increases adhesion, flexibility and permeability
EASY TO APPLY (ARMAWALL)	Easily trowelled on, or can be pumped and sprayed. Works and looks like traditional cement render
ALL WEATHER PROTECTION (ARMAWALL)	Applying a complete Armawall system will provide a long lasting durable surface
VERSATILE (ARMAWALL)	Ideal for small domestic areas, to large commercial masonry walls

DATASHEET

PRODUCT SPECIFICATIONS

SPREAD RATE	2-4/m ² (depending on substrate)
DRY TIMES: TOUCH DRY	2-4 hours at 23°
DRY TIMES: RECOAT	6-8 hours
20KG AVAILABLE SIZES	20kg
SDS	SDS available at www.ppgmsds.com.au

Surface Preparation

GENERAL-ARMAWALL	Surface preparation is the responsibility of the Applicator, Builder, Renovator or Main Contractor. Armawall Surface Preparation Products are designed to perform at their optimum when used as part of an Armawall Texture Coating System.
-------------------------	---

APPLICATION

APPLICATION	Surface should be wet down before application. Apply Taubmans Armawall Render Coarse at a thickness of 4mm - 10mm with a hawk and steel trowel. It is recommended that application be carried out by a skilled applicator and good plastering practices must be adhered to, i.e. curing of finished work and the provision of expansion joints. The use of Taubmans Armawall Sealer Bonder is recommended for use on dense substrates like Tilt Up or Pre Cast concrete panels. Please refer to data sheets for specific application details.
MIXING RATES	For traditional hawk and trowel hand application: Making sure to add powder to liquid, mix 20kg of Taubmans Armawall Render Coarse to a clean drum containing 4 to 4.5L of clean water. Consider weather conditions and adjust amount of water accordingly. Mix continually until no lumps are present. Allow mixture to stand and activate for 2 minutes, stir again then apply.
APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS	10
APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS	35
MINIMUM FILM THICKNESS	4mm
MAXIMUM FILM THICKNESS	10mm

PRECAUTIONS

GENERAL SAFETY INFORMATION ARMAWALL	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area above ground level. Do not store below 5 deg C temperature. Do not keep open bags. These should be disposed of.
--	--

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of

DATASHEET

profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au