

DATASHEET

# Taubmans Professional Ceiling Elusive White

# TAUBMANS

Product Code:  
278010



## Taubmans Professional Ceiling Elusive White

Taubmans Professional Ceiling Elusive White is specifically designed to give a dead flat finish which hides surface imperfections and also minimises banding on new plasterboard. It is easy to apply with minimum splatter and has high opacity.

## USES

Ideal for interior & exterior sheltered ceilings

## FEATURES AND BENEFITS

<b>FLAT FINISH</b>	Gives a flat finish with excellent surface defect hiding properties.
<b>HIGH OPACITY</b>	Excellent hiding properties.
<b>WATER BASED FORMULA</b>	Easy clean up with water
<b>FAST DRYING</b>	Assist project completion timelines with fast drying properties
<b>EASY TO APPLY</b>	Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.
<b>AUSTRALIAN MADE</b>	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.

## PRODUCT SPECIFICATIONS

<b>WHITE BASE</b>	Tint your desired colour from a White base
<b>FLAT</b>	Designed to produce flat uniform finish with no roller marks
<b>15L AVAILABLE SIZES</b>	15L
<b>DRY TIMES: RECOAT</b>	2 hours

DATASHEET

<b>DRY TIMES: TOUCH DRY</b>	30 mins
<b>SDS</b>	SDS available from the Taubmans Website <a href="http://taubmans.com.au">taubmans.com.au</a>
<b>VOC LEVELS</b>	30g/Litre
<b>GLOSS LEVEL</b>	1-2 at 60° (% at a 60 degree angle)

**SURFACE PREPARATION**

<b>NEW/BAREWORK</b>	Seal bare wallboards with Taubmans 3in1. Seal set plaster with Prep Right (Acrylic) Plaster Sealer
<b>AFTER PAINTING</b>	Avoid exposure to steam for 48 hours. Surface may be washed after 7 days, but always avoid abrasive cleaners.
<b>RECOATHUMIDITYPERCENTAGE</b>	50 (%)
<b>RECOATTEMPDEGREES</b>	25 (°C)
<b>TEMPERATURE MAX</b>	35 (°C)
<b>TEMPERATURE MIN</b>	10 (°C)

**APPLICATION**

<b>DRY FILM THICKNESS</b>	25 - 30 microns
<b>WET FILM THICKNESS</b>	60 - 65 microns
<b>BRUSH, ROLLER, SPRAY</b>	Apply one or two coats (as per recommendation) by roller, brush or spray gun, with the recommended RECOAT time between each coat (refer to product spec). Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.
<b>COATS REQUIRED</b>	Two
<b>CURING</b>	Avoid exposure to steam and condensation for 48 hours after painting.
<b>NAP ROLLER</b>	10mm - 12mm Pile Roller
<b>COVERAGE</b>	Up to 16m <sup>2</sup> /litre, depending on the nature of the surface. Coverage on rough or absorbent surfaces will be lower. The first coat on gyprock will be approx 10m <sup>2</sup> /litre.

**PRECAUTIONS**

<b>ENVIRONMENT INFORMATION</b>	Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit <a href="http://paintback.com.au">paintback.com.au</a>
<b>FIRST AID INFORMATION</b>	IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately. EYE CONTACT - Flush with plenty of water. Always seek medical advice. SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.

## DATASHEET

INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.

AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686  
Further information: [www.taubmans.com.au](http://www.taubmans.com.au)

### GENERAL SAFETY INFORMATION

#### WALL PAINTS

##### SAFETY

Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

#### CEILING

##### SAFETY

Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

## DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

## CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)