

DATASHEET

# Taubmans Moroka Bag & Paint Wall Treat

# TAUBMANS

Product Code:  
303510

## Taubmans Moroka Bag & Paint Wall Treat



Taubmans Moroka is a pre coloured 2 coat efflorescence-resisting system which is designed to give a medium profile "bag and paint" effect, whilst bridging hairline cracks in masonry surfaces. As a technologically advanced coating system for bricks, blocks, concrete, cement render, and masonry walls, applying Moroka by "mitt" is a faster and more economical way to achieve this finish.

## USES

Recommended for use on flush mortar brick walls, concrete and cement render, and fibre cement infills.

## FEATURES AND BENEFITS

<b>EASY TO APPLY</b>	Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.
<b>ALL WEATHER PROTECTION</b>	Built with advanced UV protection technology to resists cracking & peeling from harsh weather conditions longer
<b>FLEXIBLE</b>	Withstands normal substrate movements
<b>FAST DRYING</b>	Assist project completion timelines with fast drying properties
<b>PRE-MIXED ACRYLIC RENDER</b>	Resists cracking, crazing and drummy render issues associated with traditional sand & cement renders.
<b>AUSTRALIAN MADE</b>	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
<b>TINTABLE</b>	Tintable to over 10,000 colours. Order A4 samples or brush outs online at <a href="https://www.taubmans.com.au/specifiers/explore#search">https://www.taubmans.com.au/specifiers/explore#search</a>
<b>ACRYLIC BINDER</b>	Superior adhesion, flexibility, gloss retention & durability
<b>WATER BASED FORMULA</b>	Easy clean up with water

## PRODUCT SPECIFICATIONS

## DATASHEET

<b>VOC LEVELS</b>	<50g/Litre
<b>DRY TIMES: TOUCH DRY</b>	30 mins
<b>DRY TIMES: RECOAT</b>	2 hours
<b>15L AVAILABLE SIZES</b>	15l
<b>SDS</b>	SDS available from the Taubmans Website <a href="http://taubmans.com.au">taubmans.com.au</a>
<b>EXTENSIVE COLOUR RANGE</b>	Tintable to over 10,000 colours. Order A4 samples or brush outs online at <a href="https://www.taubmans.com.au/specifiers/explore#search">https://www.taubmans.com.au/specifiers/explore#search</a>
<b>ACCENT BASE</b>	Tint your desired colour from an Accent base

## SURFACE PREPARATION

<b>GENERAL EXTERIOR</b>	Can include exterior walls, cement render / masonry, trim, timber, galvanised iron, PVC piping and steel
<b>NEW WORK</b>	<p><b>TIMBER</b> Weathered (greyed) timber must be sanded to the original timber surface. Tannin rich timbers such as cedar should be primed with Taubmans 3 in 1 Prep or a suitable Taubmans oil based wood primer.</p> <p><b>GALVANISED IRON</b> Thoroughly degrease new surfaces. Weathered surfaces should be thoroughly cleaned before painting. For structural galvanised iron, abrade with 240 grade paper to remove chemical treatments and allow full adhesion.</p> <p><b>CEMENT RENDER / MASONRY</b> Allow masonry, cement render and mortar to cure for 28 days before painting.</p> <p><b>STEEL</b> Remove rust and prime with a suitable Taubmans iron &amp; steel primer or White Knight Rust Guard® Metal Primer.</p> <p><b>ZINCALUME® STEEL</b> Wash with water and mild detergent. Surface must be clean and dry. Apply one coat of Taubmans 3 in 1 Prep.</p>
<b>PREVIOUSLY PAINTED</b>	Remove all loose and flaking paint. Apply Taubmans 3 in 1 Prep to aged enamel systems to provide intercoat adhesion.
<b>TEMPERATURE MIN</b>	10 (°C)
<b>TEMPERATURE MAX</b>	35 (°C)
<b>RECOATTEMPDEGREES</b>	25 (°C)
<b>RECOATHUMIDITYPERCENTAGE</b>	50 (%)

## APPLICATION

<b>WET FILM THICKNESS</b>	70 - 75 microns
<b>DRY FILM THICKNESS</b>	15-20 microns

## DATASHEET

<b>BRUSH, ROLLER, SPRAY</b>	Apply two coats by roller, brush or spray gun, with 2 hours between each coat. Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.
<b>NAP ROLLER</b>	10mm - 12mm Pile Roller
<b>COVERAGE</b>	4 -8 m2/litre
<b>MAINTENANCE - DECKING</b>	No
<b>APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS</b>	10
<b>APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS</b>	35
<b>COATS REQUIRED</b>	One

## PRECAUTIONS

<b>GENERAL SAFETY INFORMATION</b>	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area. Do not store below 5 deg C temperature. Keep containers sealed when not in use
<b>FIRST AID INFORMATION</b>	<p>IF SWALLOWED</p> <p>Do NOT induce vomiting. Seek medical advice immediately.</p> <p>EYE CONTACT</p> <p>Flush with plenty of water. Always seek medical advice.</p> <p>SKIN CONTACT</p> <p>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.</p> <p>INHALATION</p> <p>Remove to fresh air, seek medical advice if breathing is laboured.</p> <p>AUSTRALIA</p> <p>24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: <a href="http://www.taubmans.com.au">www.taubmans.com.au</a></p>
<b>ENVIRONMENT INFORMATION</b>	Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit <a href="http://paintback.com.au">paintback.com.au</a>

## DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

## CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)