

DATASHEET

# Taubmans Prep Right Plaster Treatment

# TAUBMANS

Product Code:  
111525



## Taubmans Prep Right Plaster Treatment

A special acid treatment for fresh plaster that reduces alkalinity and stabilises the powdery surface to give a sound base for painting.

### USES

Fresh plaster surfaces with pH in the range of 10-12. If pH is greater than 12 then no treatment should occur until pH drops to 12. If pH is less than 10 then thinned Prep Right Plaster Sealer should be used in place of Plaster Treatment. Plaster Treatment improves adhesion of paints to fresh plaster - a mild fizzing action confirms that it is working. If the job is big, it is good practice to apply a trial patch of the paint system and check adhesion. Apply by brush or roller to thoroughly wet the surface. Do not rinse off.

### FEATURES AND BENEFITS

<b>AUSTRALIAN MADE</b>	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
<b>AUSTRALIAN STANDARD</b>	AS2311
<b>WATER BASED FORMULA</b>	Easy clean up with water

### PRODUCT SPECIFICATIONS

<b>VOC LEVELS</b>	<1g/Litre
<b>DRY TIMES: TOUCH DRY</b>	6 hours
<b>DRY TIMES: RECOAT</b>	Recoat after 24 hours at 25°C and 50% relative humidity.
<b>SDS</b>	SDS available from the Taubmans Website <a href="http://taubmans.com.au">taubmans.com.au</a>

### SURFACE PREPARATION

## DATASHEET

**NEW/BAREWORK** All surfaces must be clean and dry with all defects sanded smooth.

**TEMPERATURE MIN** 10 (°C)

**TEMPERATURE MAX** 35 (°C)

**RECOATTEMPDEGREES** 25 (°C)

**RECOATHUMIDITYPERCENTAGE** 50 (%)

## APPLICATION

**WET FILM THICKNESS** 90 - 100 microns

**DRY FILM THICKNESS** 25 - 30 microns

**NAP ROLLER** 10mm - 12mm Pile Roller

**COVERAGE** Up to 10 m<sup>2</sup>/litre.

**APPLICATION TEMPERATURE  
MINIMUM DEGREES CELCIUS** 10

**APPLICATION TEMPERATURE  
MAXIMUM DEGREES CELCIUS** 35

**COATS REQUIRED** One

## PRECAUTIONS

### GENERAL SAFETY INFORMATION

#### WALL PAINTS

#### SAFETY

Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes; wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

#### CEILING

#### SAFETY

Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

**DANGER CORROSIVE** DANGER - CORROSIVE

### FIRST AID INFORMATION

IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.

EYE CONTACT - Flush with plenty of water. Always seek medical advice.

SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.

INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.

AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686  
Further information: [www.taubmans.com.au](http://www.taubmans.com.au)

**DATASHEET****ENVIRONMENT  
INFORMATION**

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit [paintback.com.au](http://paintback.com.au)

**ENVIRONMENT & SAFETY****WARRANTY INFORMATION**

Taubmans paint that fails to give satisfactory results on properly prepared surfaces when applied according to printed directions, will be replaced.

**DISCLAIMER**

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

**CUSTOMER SERVICE/COMPANY CONTACT**

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)