

DATASHEET

Taubmans Armawall ArmaPatch Smooth

TAUBMANS

Product Code:
315024

Taubmans Armawall ArmaPatch Smooth

Taubmans Armawall Smooth Patch is a specially formulated premium quality acrylic based filling and patching compound used to repair defects in concrete, most masonry surfaces and previously painted surfaces. Armawall Smooth Patch is easily sanded to a fine, smooth finish.

USES

For the filling, repairing and patching of small defects, depressions and fine cracks up to 3mm in exterior cementitious substrates and surfaces, to produce a consistent smooth surface ready for coating. Armawall Smooth Patch must be mixed with 10% grey cement powder when being applied externally.

FEATURES AND BENEFITS

EASY SANDING (ARMAWALL)	Easily sanded acrylic patching compound
WATER BASED FORMULA	Easy clean up with water
EXCELLENT ADHESION	Provides excellent adhesion to difficult surfaces.
INTERNAL AND EXTERNAL	Suitable for use in internal and external areas
SMOOTH FINISH (ARMAWALL)	Designed for patching holes, form joints & minor imperfections in concrete or masonry walls up to 3mm in depth, where a smooth finish is required.

PRODUCT SPECIFICATIONS

15L AVAILABLE SIZES	15L
DRY TIMES: RECOAT	Sanding/ Recoat : 16 Hours. Note: This may be lengthened in damp, cold or humid conditions. Do not apply at temperatures below 10°C.
SDS	SDS available from the Taubmans Website taubmans.com.au
DRY TIMES: TOUCH DRY	Set up time : 4 Hours

DATASHEET

Surface Preparation

GENERAL EXTERIOR (ARMAWALL)	Can include exterior surfaces made of concrete, brick, blockwork, AAC block or panels
NEW CEMENT RENDER MASONRY & CONCRETE (ARMAWALL)	New cement render, masonry and concrete surfaces should be allowed to cure for 28 days. Off form concrete should be thoroughly cleaned by acid etching, water or sand blasting to ensure all bond breaker oils are removed. Aged concrete masonry and fibro surfaces in sound condition should be scrubbed down with detergent and fresh water, fresh water washed and allowed to dry. Surface irregularities such as blow holes and profile defects may require patching with Armawall Smooth Patch or Armawall Coarse Patch prior to system application.
PREVIOUSLY PAINTED (ARMAWALL)	Wash down all surfaces to remove any loose, powdery, flaky material or any other surface contaminants that may be present. Allow to dry. Apply Armawall Primer undiluted by brush, roller or spray to the surface prior to applying the specified Armawall Texture Coating System.

SURFACE PREPARATION

TEMPERATURE MAX	35 (°C)
TEMPERATURE MIN	10 (°C)
RECOATTEMPDEGREES	25 (°C)
RECOATHUMIDITYPERCENTAGE	50 (%)
SUBSTRATE MOISTURE CONTENT (ARMAWALL)	Moisture content of the substrate must be no greater than 15% wood-moisture-equivalent (WME) prior to or during application, to ensure optimal coating system performance

APPLICATION

ODOUR	Low. Ensure adequate ventilation during use.
FINISHING	This product is a surface preparation product only, as such it should be used in conjunction with the complete Armawall Texture System and specification. As a surface preparation product it should not be left exposed for more than 14 days of curing. The finishing system should be applied in a continual time frame, please refer to the Armawall Product Data Sheet for drying times.
STAINLESS STEEL TROWEL	Working in an upward action, hold trowel & material against wall and evenly apply material. Working across the wall, in a horizontal action continue to spread the material evenly.
APPLICATION	Generally Armawall Smooth Patch is applied using a trowel. Do not add cement unless being used externally. If being used externally add 10% cement by weight to compound prior to its application.
MIXING RATES	For ease of mixing cement powder into the Armawall Smooth Patch: Add cement powder to a little clean water (1 part water to 2 parts grey cement powder), use this 'slurry' mix and slowly add it to the Armawall Smooth Patch whilst stirring.

PRECAUTIONS

FIRST AID INFORMATION	<p>IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.</p> <p>EYE CONTACT - Flush with plenty of water. Always seek medical advice.</p> <p>SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.</p> <p>INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.</p> <p>AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au</p>
------------------------------	---

DATASHEET**ENVIRONMENT
INFORMATION ARMAWALL**

Do not pour leftover mixed render or any unused render powder down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations.

**GENERAL SAFETY
INFORMATION ARMAWALL**

Store in original container protected from direct sunlight in a dry, cool and well-ventilated area above ground level. Do not store below 5 deg C temperature. Do not keep open bags. These should be disposed of.

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au