

DATASHEET

Taubmans Armawall Sand

TAUBMANS

Product Code:
310310



Taubmans Armawall Sand

Taubmans Armawall Sand provides a premium exterior matt finish. It is a heavy duty, high build texture containing fine aggregates, which helps hide minor surface defects. Armawall Sand can be applied in various patterns and styles for that modern fine cement rendered look. For extra durability and substrate protection, Armawall Sand can be overcoated with Armawall Armashield or Satin.

USES

Exterior cement render, masonry, fibrous cement sheeting, bricks and blockwork.

FEATURES AND BENEFITS

CONTAINS AGGREGATES	Hides minor surface defects
HIGH BUILD (ARMAWALL)	Build up to 12mm (or 24mm in 2 coats)
APAS APPROVED	Australian Standard AS2311.
FLEXIBLE	Withstands normal substrate movements
AUSTRALIAN MADE	Our Aussie Heritage: Since our creation over a century ago in 1897 by George Henry Taubman, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success with our state-of-the-art plant in Clayton, VIC.
WATER BASED FORMULA	Easy clean up with water

PRODUCT SPECIFICATIONS

ABRASION RESISTANCE	Excellent Abrasion resistance
DRY TIMES: RECOAT	4 hours Note: This may be lengthened in damp, cold or humid conditions.
15L AVAILABLE SIZES	15L

DATASHEET

SDS	SDS available at www.ppgmsds.com.au
WHITE BASE	Tint your desired colour from a White base
WATER RESISTANT	Excellent water resistance
WEATHERING	Excellent weather resistance when applied as part of an approved Taubmans Armawall texture system

SURFACE PREPARATION

AGED ENAMEL	Previously painted enamel surfaces should be undercoated with Taubmans Prep Right Traditional Undercoat
MASONRY SURFACES	<p>Fresh cementitious substrates should be left to cure for 28 days before painting. There must be less than 15% moisture content at the surface prior to and during application.</p> <p>Surface irregularities such as blow holes and profile defects may require patching with Armawall Smooth Patch or Armawall Coarse Patch prior to system application.</p> <p>Prime cement render, off-form concrete, AAC, blockwork & brickwork with Armawall Primer. Prime Tilt-up concrete, GRC and CFC with Armawall Sealer Bonder.</p>
SUBSTRATE MOISTURE CONTENT (ARMAWALL)	Moisture content of the substrate must be no greater than 15% wood-moisture-equivalent (WME) prior to or during application, to ensure optimal coating system performance
TEMPERATURE MIN	10 (°C)
TEMPERATURE MAX	35 (°C)
GENERAL PREPARATION	All surfaces must be free of dirt, dust, grease, oil, mould release agents, bond breakers and any other contaminants that may interfere with adhesion.

Surface Preparation

GENERAL-ARMAWALL	Surface preparation is the responsibility of the Applicator, Builder, Renovator or Main Contractor. Armawall Surface Preparation Products are designed to perform at their optimum when used as part of an Armawall Texture Coating System.
-------------------------	---

APPLICATION

APPLICATION	Armawall Sand should be applied in two coats using a texture roller. A black mesh roller will provide a medium profile or spaghetti roller will provide a high profile
WET FILM THICKNESS	500-600 microns
DRY FILM THICKNESS	400-500 microns
STIRRING	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
COVERAGE	2 m ² /litre

DATASHEET

APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS	10
APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS	35
COATS REQUIRED	One or Two
OVERCOATING	Can be overcoated with Armawall Armashield or Armawall Satin for enhanced exterior durability.

PRECAUTIONS

GENERAL SAFETY INFORMATION	WALL PAINTS SAFETY	Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.
	CEILING SAFETY	Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.
FIRST AID INFORMATION	IF SWALLOWED	- Do NOT induce vomiting. Seek medical advice immediately.
	EYE CONTACT	- Flush with plenty of water. Always seek medical advice.
	SKIN CONTACT	- Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.
	INHALATION	- Remove to fresh air, seek medical advice if breathing is laboured.
	AUSTRALIA	- 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au
ENVIRONMENT INFORMATION		Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

VERSION

VERSION DATE	16 May 2025
VERSION NUMBER	1.1

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au