

DATASHEET

# Taubmans Sunproof Exterior Semi Gloss

# TAUBMANS

Product Code:  
113400



## Taubmans Sunproof Exterior Semi Gloss

Sunproof- Exterior by Taubmans- was created with the Australian sun in mind. Formulated with UV barriers, Sunproof protects your home from the sun's ageing e-effects and has a 25 year guarantee against flaking, peeling and blistering.\* This water based paint is fast drying, self-priming and only requires 2 coats on previously painted surfaces, so you can get the job done fast and right the first time. For superior sun protection, Sunproof your home.

**25 Year Guarantee**  
AGAINST FLAKING, PEELING & BLISTERING\*



## USES

All exterior walls and trim including timber, galvanised iron, Zinc, masonry, weatherboard, cement render, fibrous cement, brick, fences, pergolas, and outdoor timber furniture.

## FEATURES AND BENEFITS

|                           |   |
|---------------------------|---|
| <b>AUSTRALIAN MADE</b>    | Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC. |
| <b>FAST DRYING</b>        | Assist project completion timelines with fast drying properties   |
| <b>EASY TO APPLY</b>      | Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.   |
| <b>SELF-PRIMING</b>       | In most cases, removes the need for a prep coat   |
| <b>HIGH OPACITY</b>       | Excellent hiding properties.  |
| <b>FLEXIBLE</b>           | Withstands normal substrate movements   |
| <b>TINTABLE</b>           | Tintable to over 10,000 colours. Order A4 samples or brush outs online at <a href="https://www.taubmans.com.au/specifiers/explore#search">https://www.taubmans.com.au/specifiers/explore#search</a>                             |
| <b>WEATHER RESISTANCE</b> | Provides advanced protection against the extremes of weather  |
| <b>ACRYLIC BINDER</b>     | Superior adhesion, flexibility, gloss retention & durability  |

## DATASHEET

**WATER BASED FORMULA** Easy clean up with water

**AUSTRALIAN STANDARD** AS/NZS 4020:2018

## PRODUCT SPECIFICATIONS

**4L AVAILABLE SIZES** 4L

**10L AVAILABLE SIZES** 10L

**ACCENT BASE** Tint your desired colour from an Accent base

**WHITE BASE** Tint your desired colour from a White base

**NEUTRAL BASE** Tint your desired colour from a Neutral base

**DRY TIMES: RECOAT** 2 hours

**DRY TIMES: TOUCH DRY** 30 minutes

**DRY FILM THICKNESS** 25 – 30 microns

**WET FILM THICKNESS** 60 – 65 microns

**GLOSS LEVEL**  
20 - 25 (% at a 60 degree angle)

**VOC LEVELS** 49 g/L

## SURFACE PREPARATION

**GENERAL EXTERIOR** Can include exterior walls, cement render / masonry, trim, timber, galvanised iron, PVC piping and steel

**RECOAT HUMIDITY PERCENTAGE** 25 (%)

**TEMPERATURE MAX** 35 (°C)

**TEMPERATURE MIN** 10 (°C)

### NEW WORK

#### TIMBER

Weathered (greyed) timber must be sanded to the original timber surface. Tannin rich timbers such as cedar may require two coats or use Taubmans Oil Based Wood Primer.

#### GALVANISED IRON

Thoroughly degrease new surfaces. Weathered surfaces should be thoroughly cleaned before painting. For structural galvanised iron, abrade with 240 grade paper to remove chemical treatments and allow full adhesion.

#### CEMENT RENDER / MASONRY

Allow masonry, cement render and mortar to cure for 28 days before painting.

#### STEEL

**DATASHEET**

Remove rust and prime with a suitable Taubmans iron & steel primer or White Knight Rust Guard® Metal Primer.

ZINCALUME® STEEL

Wash with water and mild detergent. Surface must be clean and dry. Apply one coat of Taubmans 3 in 1 Prep.

**PREVIOUSLY PAINTED**

Remove all loose and flaking paint. Apply Taubmans 3 in 1 Prep to aged enamel systems to provide intercoat adhesion.

**RAINWATER COLLECTION PREP**

Ensure surface is clean, dry and free from all dirt, dust, grease, oil, rust and any other surface contamination. Prior to painting, disconnect all down pipes or methods of water collection. Do not apply a primer. Leave downpipes disconnected for at least 1 week after painting. Rinse painted roof thoroughly with a hose, allow to dry, and repeat. Reconnect downpipes. Alternatively downpipes may be reconnected after heavy rainfall (>10mm in 24 hours).

**APPLICATION**

**STIRRING**

Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency

**NAP ROLLER**

10mm - 12mm Pile Roller

**COVERAGE**

Up to 16m<sup>2</sup>/litre. Coverage will be lower on rough or absorbent surfaces.

**COATS REQUIRED**

2

**PRECAUTIONS**

**GENERAL SAFETY INFORMATION**

**WALL PAINTS**

**SAFETY**

Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

**CEILING**

**SAFETY**

Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

**FIRST AID INFORMATION**

IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.

EYE CONTACT - Flush with plenty of water. Always seek medical advice.

SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.

INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.

AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686  
Further information: [www.taubmans.com.au](http://www.taubmans.com.au)

**ENVIRONMENT & SAFETY**

**WARRANTY INFORMATION**

Taubmans SunProof Exterior is guaranteed against blistering, flaking or peeling if applied on suitable and properly prepared surfaces according to printed directions. This guarantee applies to the owner of the house/property to which the paint has been applied and is available as long as the owner owns and lives in the house/property. The benefits provided under this guarantee are not transferable. Proof of purchase is required. This guarantee is given by PPG Industries Australia Pty Limited. This guarantee only applies to residential properties within Australia. This guarantee applies to defects in the manufacture or formulation of the paint and

**DATASHEET**

does not cover paint failure caused by factors beyond our control. If this guarantee is not met, we will replace the paint or refund your money. We are not liable for the cost of labour or any other direct or indirect loss or damage arising from a breach of this guarantee. Customers are responsible for all costs of claiming under this guarantee. To claim, customers must write to us or call our Customer Service number to request a claim form. The benefits provided by this guarantee are in addition to other rights and remedies under the law. If you are a consumer within the meaning of the Australian Consumer Law: Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

**DISCLAIMER**

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

**CUSTOMER SERVICE/COMPANY CONTACT**

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)