

DATASHEET

# Taubmans Oil Based Enamel Gloss

# TAUBMANS

Product Code:  
120930



## Taubmans Oil Based Enamel Gloss

Classic Oil Based enamel, designed for high traffic areas. Suitable for all interior timber and metal applications where a smooth gloss or semi gloss finish is desired.  
INTERIOR ENAMEL • Smooth Finish • Tough & Hard Wearing • Superior Washability • Resists Abrasion

## USES

Suitable for all interior and exterior doors, trims and windows.

## FEATURES AND BENEFITS

<b>SCRUB RESISTANT</b>	Provides a tough and durable abrasion-resistant coating
<b>ADVANCED WASHABILITY</b>	Resists burnishing – the formation of shiny patches on washing.
<b>HIGH OPACITY</b>	Excellent hiding properties.
<b>EASY TO APPLY</b>	Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.
<b>INTERNAL AND EXTERNAL</b>	Suitable for use in internal and external areas
<b>FLEXIBLE</b>	Withstands normal substrate movements
<b>AUSTRALIAN MADE</b>	Our Aussie Heritage: Since our creation over a century ago in 1897 by George Henry Taubman, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success with our state-of-the-art plant in Clayton, VIC.
<b>TINTABLE</b>	Tintable to over 10,000 colours. Order A4 samples or brush outs online at <a href="https://www.taubmans.com.au/specifiers/explore#search">https://www.taubmans.com.au/specifiers/explore#search</a>
<b>AUSTRALIAN STANDARD</b>	AS2311, AS3730.6, AS3730.11
<b>ADVANCED FLOW MODIFIERS</b>	Promotes ease of application, good flow properties and minimal roller splatter
<b>APAS APPROVED</b>	APAS 0015/1

DATASHEET

**PRODUCT SPECIFICATIONS**

<b>GLOSS LEVEL</b>	80-90 (% at a 60 degree angle)
<b>VOC LEVELS</b>	398g/Litre
<b>DRY TIMES: TOUCH DRY</b>	4-6 hours
<b>DRY TIMES: RECOAT</b>	16 hours
<b>1L AVAILABLE SIZES</b>	1l
<b>4L AVAILABLE SIZES</b>	4l
<b>10L AVAILABLE SIZES</b>	10l
<b>SDS</b>	SDS available at <a href="http://www.ppgmsds.com.au">www.ppgmsds.com.au</a>
<b>EXTENSIVE COLOUR RANGE</b>	Tintable to over 10,000 colours. Order A4 samples or brush outs online at <a href="https://www.taubmans.com.au/specifiers/explore#search">https://www.taubmans.com.au/specifiers/explore#search</a>
<b>WHITE BASE</b>	Tint your desired colour from a White base
<b>ACCENT BASE</b>	Tint your desired colour from an Accent base
<b>NEUTRAL BASE</b>	Tint your desired colour from a Neutral base
<b>HI-CHROMA RED BASE</b>	Tint your desired colour from a red base
<b>HI-CHROMA YELLOW BASE</b>	Tint your desired colour from a yellow base
<b>HI-CHROMA BLUE BASE</b>	Tint your desired colour from a blue base
<b>BLACK BASE</b>	Tint your desired colour from a black base
<b>MID-BRISTOL GREEN BASE</b>	Tint your desired colour from a mid-bristol green base

**SURFACE PREPARATION**

<b>GENERAL INTERIOR</b>	Can include interior walls, ceilings, doors and architraves
<b>GENERAL EXTERIOR</b>	Can include exterior walls, cement render / masonry, trim, timber, galvanised iron, PVC piping and steel
<b>NEW WORK</b>	<p><b>TIMBER</b></p> <p>Weathered (greyed) timber must be sanded to the original timber surface. Tannin rich timbers such as cedar may require two coats or use Taubmans Oil Based Wood Primer.</p> <p><b>GALVANISED IRON</b></p> <p>Thoroughly degrease new surfaces. Weathered surfaces should be thoroughly cleaned before painting. For structural galvanised iron, abrade with 240 grade paper to remove chemical treatments and allow full adhesion.</p>

**DATASHEET**

**CEMENT RENDER / MASONRY**

Allow masonry, cement render and mortar to cure for 28 days before painting.

**STEEL**

Remove rust and prime with a suitable Taubmans iron & steel primer or White Knight Rust Guard® Metal Primer.

**ZINCALUME® STEEL**

Wash with water and mild detergent. Surface must be clean and dry. Apply one coat of Taubmans 3 in 1 Prep.

<b>PREVIOUSLY PAINTED</b>	Remove all loose and flaking paint. Apply Taubmans 3 in 1 Prep to aged enamel systems to provide intercoat adhesion.
<b>TEMPERATURE MIN</b>	10 (°C)
<b>TEMPERATURE MAX</b>	35 (°C)
<b>RECOATTEMPDEGREES</b>	25 (°C)
<b>RECOATHUMIDITYPERCENTAGE</b>	50 (%)

**APPLICATION**

<b>BRUSH, ROLLER, SPRAY</b>	Apply 1 or 2 coats (as per recommendation) by roller, brush or spray gun, with 16 hours between each coat. Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.
<b>WET FILM THICKNESS</b>	60 -65 microns
<b>DRY FILM THICKNESS</b>	25 - 30 microns
<b>STIRRING</b>	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
<b>NAP ROLLER</b>	7mm Mohair Roller
<b>CURING</b>	Avoid exposure to steam and condensation for 48 hours after painting.
<b>COVERAGE</b>	Up to 16m <sup>2</sup> /litre.
<b>APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS</b>	10
<b>APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS</b>	35
<b>COATS REQUIRED</b>	Two

**PRECAUTIONS**

<b>GENERAL SAFETY INFORMATION</b>	<p><b>WALL PAINTS SAFETY</b></p> <p>Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p>
-----------------------------------	---

**DATASHEET**

CEILING

SAFETY

Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

**DANGER FLAMMABLE LIQUID AND VAPOUR**

Warning. Flammable hydrocarbon liquid. Keep out of reach of children. Keep lid on when not in use.

Wear solvent resistant gloves and eye protection when using. Ensure adequate ventilation and do not breathe vapour.

**FIRST AID INFORMATION**

IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.

EYE CONTACT - Flush with plenty of water. Always seek medical advice.

SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.

INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.

AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686  
Further information: [www.taubmans.com.au](http://www.taubmans.com.au)

**ENVIRONMENT INFORMATION**

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit [paintback.com.au](http://paintback.com.au)

**ENVIRONMENT & SAFETY**

**WARRANTY INFORMATION**

The Australian Paint Manufacturers' Federation has issued the following general warning to assist specifiers and end users understanding one of the key characteristics of oil based paint. All white and pale coloured enamels will yellow with age. These enamels will yellow more rapidly in areas of low natural light, when applied in poorly ventilated conditions, or in the presence of ammonia - common in water based paints and some household chemicals. Only the use of water based acrylics can assure resistance to yellowing.

**DISCLAIMER**

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

**CUSTOMER SERVICE/COMPANY CONTACT**

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)