

DATASHEET

# Taubmans Armawall Ultrafine Flat

# TAUBMANS

Product Code:  
310230



## Taubmans Armawall Ultrafine Flat

Taubmans Armawall Ultrafine Flat is a durable exterior matt acrylic finish providing a low profile cement render effect. Ultrafine Flat can bridge hairline cracks in masonry surfaces with its fibre reinforced formula. It can be left as a matt finish, or can be over coated with Armawall Armashield or Armawall Satin for extra durability and substrate protection.

## USES

Brick, fibre cement, masonry, cement render and other masonry surfaces. DO NOT use on timber surfaces.  
Recommended for Exterior

## FEATURES AND BENEFITS

<b>ADHESION PROMOTING POLYMERS</b>	Superior adhesion to masonry surfaces, no primer required
<b>MOULD RESISTANT</b>	Helps prevent the growth of mould, mildew and fungus in damp areas
<b>FLAT FINISH</b>	Gives a flat finish with excellent surface defect hiding properties.
<b>AUSTRALIAN MADE</b>	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
<b>ACRYLIC BINDER</b>	Superior adhesion, flexibility, gloss retention & durability
<b>WATER BASED FORMULA</b>	Easy clean up with water

## PRODUCT SPECIFICATIONS

<b>PROFILE</b>	Low Texture Profile – Contemporary render-like finish.
<b>FIBRE REINFORCED</b>	Stronger film with greater durability
<b>CLEAN UP</b>	Water, away from drains and watercourses.
<b>GLOSS LEVEL</b>	1-2 at 60° (% at a 60 degree angle)

## DATASHEET

<b>VOC LEVELS</b>	< 50%
<b>DRY TIMES: TOUCH DRY</b>	60 mins
<b>DRY TIMES: RECOAT</b>	4 hours
<b>15L AVAILABLE SIZES</b>	15l
<b>SDS</b>	SDS available from the Taubmans Website <a href="http://taubmans.com.au">taubmans.com.au</a>
<b>WHITE BASE</b>	Tint your desired colour from a White base
<b>NEUTRAL BASE</b>	Tint your desired colour from a Neutral base

## SURFACE PREPARATION

<b>MASONRY SURFACES</b>	New cement render, masonry and concrete surfaces should be allowed to cure for 28 days. Off form concrete should be thoroughly cleaned by acid etching, water or sand blasting to ensure all bond breaker oils are removed. Seal tilt slab concrete and CFC with Armawall Sealer Bonder thinned 50% with i coat LO - 2 Thinner to ensure adhesion of topcoats. Previously painted surfaces in sound condition should be scrubbed down with detergent and fresh water and allowed to dry. Previously painted enamels surfaces should be undercoated with Taubmans Prepright Traditional undercoat. Surface irregularities such as blow holed and profile defects may require patching with Armawall Coarse or Smooth patch prior to system application. CAUTION: When applying Armawall Ultrafine flat on large tilt-up concrete slabs or unbroken high rise off form concrete, you will not easily be able to maintain a wet edge. This may cause overlaps to stand out.
<b>SUBSTRATE MOISTURE CONTENT (ARMAWALL)</b>	Moisture content of the substrate must be no greater than 15% wood-moisture-equivalent (WME) prior to or during application, to ensure optimal coating system performance
<b>TEMPERATURE MIN</b>	10 (°C)
<b>TEMPERATURE MAX</b>	35 (°C)
<b>RECOATTEMPDEGREES</b>	25 (°C)
<b>RECOATHUMIDITYPERCENTAGE</b>	50 (%)

## APPLICATION

<b>APPLICATION</b>	Apply 2 coats of Armawall Ultrafine Flat using a long nap roller.
<b>WET FILM THICKNESS</b>	140 -150 microns
<b>DRY FILM THICKNESS</b>	90 - 100 microns
<b>STIRRING</b>	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
<b>COARSE TEXTURE ROLLER</b>	Yes
<b>NAP ROLLER</b>	Long Nap Roller

## DATASHEET

<b>COVERAGE</b>	6 m2/litre, depending on surface profile
<b>APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS</b>	10
<b>APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS</b>	35
<b>COATS REQUIRED</b>	One or Two

## PRECAUTIONS

<b>GENERAL SAFETY INFORMATION</b>	<b>WALL PAINTS SAFETY</b>	Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.
	<b>CEILING SAFETY</b>	Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.
<b>FIRST AID INFORMATION</b>	<b>IF SWALLOWED</b>	- Do NOT induce vomiting. Seek medical advice immediately.
	<b>EYE CONTACT</b>	- Flush with plenty of water. Always seek medical advice.
	<b>SKIN CONTACT</b>	- Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.
	<b>INHALATION</b>	- Remove to fresh air, seek medical advice if breathing is laboured.
	<b>AUSTRALIA</b>	- 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: <a href="http://www.taubmans.com.au">www.taubmans.com.au</a>
<b>ENVIRONMENT INFORMATION</b>		Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit <a href="http://paintback.com.au">paintback.com.au</a>

## DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

## CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)