

DATASHEET

# Taubmans Armawall Sealer Bonder (W)

# TAUBMANS

Product Code:  
315705



## Taubmans Armawall Sealer Bonder (W)

Armawall Sealer Bonder is a first step in the Armawall Texture Coating System which can prime, seal, or even out the substrate's absorption rate prior to the application of a texture. Sealer Bonder is a premium solvent based acrylic blend, which penetrates into masonry surfaces to promote adhesion of water based topcoats. Provides excellent intercoat adhesion to a variety of topcoats, and is fast drying so there is less time needed between coats.

## USES

Masonry, unpainted ext/int brickwork Specifically recommended for Tilt Slab Concrete and Compressed Fibrous Cement (CFC) where water base sealers are not effective. It must not be used on previously painted surfaces, or unpainted timber or metal. Also suitable for unpainted exterior/ interior brickwork, fibro, masonry- concrete and cement render.

## FEATURES AND BENEFITS

<b>EASY TO APPLY</b>	Holds a wet edge for longer and reduces roller splatter
<b>FLAT FINISH</b>	Superior hiding properties, to minimise surface imperfections
<b>FAST DRYING</b>	Assist project completion timelines with fast drying properties
<b>PENETRATIVE FORMULA</b>	Excellent wetting properties allow the coating to penetrate the surface
<b>VAPOR PERMEABILITY</b>	Allows substrate to breathe to reduce moisture entrapment
<b>AUSTRALIAN MADE</b>	Our Aussie Heritage:  Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
<b>TINTABLE</b>	Tintable to over 10,000 colours. Order A4 samples or brush outs online at <a href="https://www.taubmans.com.au/specifiers/explore#search">https://www.taubmans.com.au/specifiers/explore#search</a>
<b>AUSTRALIAN STANDARDS</b>	AS2311, AS3730.22
<b>ADVANCED FLOW MODIFIERS</b>	Promotes ease of application, good flow properties and minimal roller splatter

## DATASHEET

**ACRYLIC BINDER** Increases adhesion, flexibility and permeability

## PRODUCT SPECIFICATIONS

<b>WHITE BASE</b>	Tint your desired colour from a White base
<b>10L AVAILABLE SIZES</b>	10L
<b>DRY TIMES: RECOAT</b>	2 hours
<b>SDS</b>	SDS available from the Taubmans Website <a href="http://taubmans.com.au">taubmans.com.au</a>

## SURFACE PREPARATION

<b>WET FILM THICKNESS</b>	45 - 50 microns (Microns)
<b>DRY FILM THICKNESS</b>	20 - 25 microns (Microns)
<b>TEMPERATURE MIN</b>	10 (°C)
<b>TEMPERATURE MAX</b>	35 (°C)
<b>RECOATTEMPDEGREES</b>	25 (°C)
<b>RECOATHUMIDITYPERCENTAGE</b>	50 (%)

## APPLICATION

<b>STIRRING</b>	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
<b>AIRLESS SPRAY</b>	AIRLESS SPRAY
<b>BRUSH, ROLLER</b>	Apply two coats by roller, brush or spray gun, with 2 hours between each coat. Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.
<b>NAP ROLLER</b>	16mm Pile Roller
<b>COATS REQUIRED</b>	One

## PRECAUTIONS

<b>FIRST AID INFORMATION</b>	IF SWALLOWED Do NOT induce vomiting. Seek medical advice immediately.
	EYE CONTACT Flush with plenty of water. Always seek medical advice.

## DATASHEET

## SKIN CONTACT

Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.

## INHALATION

Remove to fresh air, seek medical advice if breathing is laboured.

## AUSTRALIA

24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)

**ENVIRONMENT  
INFORMATION**

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit [paintback.com.au](http://paintback.com.au)

**DISCLAIMER**

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

**CUSTOMER SERVICE/COMPANY CONTACT**

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)