

DATASHEET

Taubmans Armawall Patch Coarse

TAUBMANS

Product Code:
315019



Taubmans Armawall Patch Coarse

Taubmans Armawall Patch Coarse is a premium acrylic based filling and patching compound for application by trowel, filling blade or scraper. Armawall Coarse Patch is designed for filling joints in fibre cement cladding, patching of deep defects, depressions and cracks up to 8mm deep in exterior surfaces. Suitable for exterior and interior use. Armawall Coarse Patch must be mixed with 3kg of cement per 15L of patching compound prior to use. Armawall Coarse Patch is not easily sanded and is suitable for application over previously painted surfaces.

USES

Armawall Coarse Patch is used to fill joints in fibre cement sheeting and large imperfections in fibre cement sheeting, AAC, EPS, tilt slabs and block walls, etc. Armawall Coarse Patch is mixed with 20% (3kg) cement powder prior to its application.

FEATURES AND BENEFITS

EASY TO APPLY	Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.
FLAT FINISH	Gives a flat finish with excellent surface defect hiding properties.
AUSTRALIAN MADE	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
WATER BASED FORMULA	Easy clean up with water

PRODUCT SPECIFICATIONS

POT LIFE	Once mixed with 20% cement, Armawall Coarse Patch has a pot life of 2 hours. Note: This may be reduced in warm, windy conditions.
DRY TIMES: RECOAT	16 hours
15L AVAILABLE SIZES	15L
SDS	SDS available from the Taubmans Website taubmans.com.au

DATASHEET

Surface Preparation

GENERAL-ARMAWALL Surface preparation is the responsibility of the Applicator, Builder, Renovator or Main Contractor. Armawall Surface Preparation Products are designed to perform at their optimum when used as part of an Armawall Texture Coating System.

APPLICATION

MIXING RATES Armawall Coarse Patch must be mixed with 3 kg of cement powder per 15L of patching compound prior to its application.

STAINLESS STEEL TROWEL Working in an upward action, hold trowel & material against wall and evenly apply material. Working across the wall, in a horizontal action continue to spread the material evenly.

COVERAGE Variable

APPLICATION TEMPERATURE 10

MINIMUM DEGREES CELCIUS

APPLICATION TEMPERATURE 35

MAXIMUM DEGREES CELCIUS

FINISHING (ARMAWALLPATCH) This product is a surface preparation product only, as such it should be used in conjunction with the complete Armawall Texture System and specification. As a surface preparation product it should not be left exposed for more than 14 days of curing. The finishing system should be applied in a continual time frame, please refer to the Armawall Product Data Sheet for drying times.

MIXING COARSE PATCH It is recommended that enough material is mixed to be applied within the pot life of the product. The best way to mix the cement powder into the Armawall Coarse Patch is to blend the cement with a little water to produce a slurry mix. The mix is then poured into the Armawall Coarse Patch and stirred through.

PRECAUTIONS

GENERAL SAFETY INFORMATION WALL PAINTS SAFETY
Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

CEILING SAFETY
Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

FIRST AID INFORMATION IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.
EYE CONTACT - Flush with plenty of water. Always seek medical advice.
SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.
INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.
AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686
Further information: www.taubmans.com.au

ENVIRONMENT INFORMATION Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au