

DATASHEET

# Taubmans Professional Exterior Gloss

# TAUBMANS

Product Code:  
278730



## Taubmans Professional Exterior Gloss

Taubmans Professional Exterior Gloss is a premium water-based, self-priming paint, specially developed for the professional painter to provide a luxurious application feel. It delivers excellent UV protection, coverage, washability, and a professional finish.

## USES

## FEATURES AND BENEFITS

<b>SAFE FOR POTABLE WATER COLLECTION</b>	Ideal for exterior walls (recommended for weatherboards, roofs and trim), cement render / masonry, timber, galvanised iron, PVC piping and steel. Based on completion and evaluation of all tests, this product fully complies with the test requirements of AS/NZS 4020:2018 to cover a cold and hot water application up to ~80oC, at the recommended 'total immersion' exposure of ~9,146mm2 test sample / 1L test water at (80 ± 2)oC.
<b>SELF-PRIMING</b>	In most cases, removes the need for a prep coat
<b>DIRT SHEDDING FORMULA</b>	Protects surfaces and keeps them looking newer for longer by easily washing away dirt and pollutants from the surface
<b>UV PROTECTION</b>	Blocks out harmful UV rays for longer lasting results
<b>WATER BASED FORMULA</b>	Easy clean up with water
<b>FAST DRYING</b>	Assist project completion timelines with fast drying properties
<b>EASY TO APPLY</b>	Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.
<b>AUSTRALIAN MADE</b>	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
<b>TINTABLE</b>	Tintable to over 10,000 colours. Order A4 samples or brush outs online at <a href="https://www.taubmans.com.au/specifiers/explore#search">https://www.taubmans.com.au/specifiers/explore#search</a>

## PRODUCT SPECIFICATIONS

## DATASHEET

<b>4L AVAILABLE SIZES</b>	4L
<b>10L AVAILABLE SIZES</b>	10L
<b>15L AVAILABLE SIZES</b>	15L
<b>ACCENT BASE</b>	Tint your desired colour from an Accent base
<b>NEUTRAL BASE</b>	Tint your desired colour from a Neutral base
<b>WHITE BASE</b>	Tint your desired colour from a White base
<b>GLOSS LEVEL</b>	65-70 at 60° (% at a 60 degree angle)
<b>DRY TIMES: RECOAT</b>	2 hours
<b>DRY TIMES: TOUCH DRY</b>	30 mins
<b>SDS</b>	SDS available from the Taubmans Website <a href="http://taubmans.com.au">taubmans.com.au</a>
<b>VOC LEVELS</b>	49 g/Litre

## SURFACE PREPARATION

<b>RECOAT HUMIDITY PERCENTAGE</b>	50 (%)
<b>RECOAT TEMP DEGREES</b>	25 (°C)
<b>TEMPERATURE MAX</b>	35 (°C)
<b>TEMPERATURE MIN</b>	10 (°C)
<b>AFTER PAINTING</b>	Avoid exposure to steam for 48 hours. Surface may be washed after 7 days, but always avoid abrasive cleaners.
<b>NEW WORK</b>	<p><b>TIMBER</b></p> <p>Weathered (greyed) timber must be sanded to the original timber surface. Tannin rich timbers such as cedar may require two coats or use Taubmans Oil Based Wood Primer.</p> <p><b>GALVANISED IRON</b></p> <p>Thoroughly degrease new surfaces. Weathered surfaces should be thoroughly cleaned before painting. For structural galvanised iron, abrade with 240 grade paper to remove chemical treatments and allow full adhesion.</p> <p><b>CEMENT RENDER / MASONRY</b></p> <p>Allow masonry, cement render and mortar to cure for 28 days before painting.</p> <p><b>STEEL</b></p> <p>Remove rust and prime with a suitable Taubmans iron &amp; steel primer or White Knight Rust Guard® Metal Primer.</p> <p><b>ZINCALUME® STEEL</b></p> <p>Wash with water and mild detergent. Surface must be clean and dry. Apply one coat of Taubmans 3 in 1 Prep.</p>

## DATASHEET

### APPLICATION

<b>DRY FILM THICKNESS</b>	25 - 30 microns
<b>WET FILM THICKNESS</b>	60 -65 microns
<b>BRUSH, ROLLER, SPRAY</b>	Apply one or two coats (as per recommendation) by roller, brush or spray gun, with the recommended RECOAT time between each coat (refer to product spec). Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.
<b>COATS REQUIRED</b>	2
<b>NAP ROLLER</b>	10mm - 12mm Pile Roller
<b>STIRRING</b>	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
<b>COVERAGE</b>	Up to 16 square metres per litre (depending on substrate).

### PRECAUTIONS

<b>GENERAL SAFETY INFORMATION</b>	<p>WALL PAINTS</p> <p>SAFETY</p> <p>Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p>
	<p>CEILING</p> <p>SAFETY</p> <p>Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p>
<b>ENVIRONMENT INFORMATION</b>	Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit <a href="http://paintback.com.au">paintback.com.au</a>
<b>FIRST AID INFORMATION</b>	<p>IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.</p> <p>EYE CONTACT - Flush with plenty of water. Always seek medical advice.</p> <p>SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.</p> <p>INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.</p> <p>AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: <a href="http://www.taubmans.com.au">www.taubmans.com.au</a></p>

### ENVIRONMENT & SAFETY

#### WARRANTY INFORMATION

### DISCLAIMER

## DATASHEET

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

## CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: [www.taubmans.com.au](http://www.taubmans.com.au)