

DATASHEET

Taubmans Sunproof Exterior Low Sheen

TAUBMANS

Product Code:
113200



Taubmans Sunproof Exterior Low Sheen

Sunproof- Exterior by Taubmans- was created with the Australian sun in mind. Formulated with UV barriers, Sunproof protects your home from the sun's ageing e-effects and has a 25 year guarantee against flaking, peeling and blistering.* This water based paint is fast drying, self-priming and only requires 2 coats on previously painted surfaces, so you can get the job done fast and right the first time. For superior sun protection, Sunproof your home.

25 Year Guarantee
AGAINST FLAKING, PEELING & BLISTERING*



USES

Weatherboard, cement render, fibrous cement, brick, fences, pergolas, and outdoor timber furniture. Suitable for the collection of drinking water

FEATURES AND BENEFITS

HIGH OPACITY	Excellent hiding properties.
EASY TO APPLY	Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.
FAST DRYING	Assist project completion timelines with fast drying properties
SELF-PRIMING	In most cases, removes the need for a prep coat
AUSTRALIAN MADE	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
TINTABLE	Tintable to over 10,000 colours. Order A4 samples or brush outs online at https://www.taubmans.com.au/specifiers/explore#search
AUSTRALIAN STANDARD	AS/NZS 4020:2018, AS 3730.8
APAS APPROVED	APAS 0280/3
ACRYLIC BINDER	Superior adhesion, flexibility, gloss retention & durability

DATASHEET

UV PROTECTION Blocks out harmful UV rays for longer lasting results

WATER BASED FORMULA Easy clean up with water

PRODUCT SPECIFICATIONS

LOW SHEEN A subtle sheen level which is good for cleaning and hides surface imperfections better than gloss level paints.

GLOSS LEVEL 9-10 at 60° (% at a 60 degree angle)

VOC LEVELS 39g/Litre

DRY TIMES: TOUCH DRY 30 mins

DRY TIMES: RECOAT 2 hours

1L AVAILABLE SIZES 1L

4L AVAILABLE SIZES 4L

6L AVAILABLE SIZES 6L

10L AVAILABLE SIZES 10L

15L AVAILABLE SIZES 15L

SDS SDS available from the Taubmans Website taubmans.com.au

EXTENSIVE COLOUR RANGE Tintable to over 10,000 colours. Order A4 samples or brush outs online at <https://www.taubmans.com.au/specifiers/explore#search>

WHITE BASE Tint your desired colour from a White base

ACCENT BASE Tint your desired colour from an Accent base

NEUTRAL BASE Tint your desired colour from a Neutral base

SURFACE PREPARATION

GENERAL EXTERIOR Can include exterior walls, cement render / masonry, trim, timber, galvanised iron, PVC piping and steel

NEW WORK

TIMBER
Weathered (greyed) timber must be sanded to the original timber surface. Tannin rich timbers such as cedar may require two coats or use Taubmans Oil Based Wood Primer.

GALVANISED IRON
Thoroughly degrease new surfaces. Weathered surfaces should be thoroughly cleaned before painting. For structural galvanised iron, abrade with 240 grade paper to remove chemical treatments and allow full adhesion.

CEMENT RENDER / MASONRY

DATASHEET

Allow masonry, cement render and mortar to cure for 28 days before painting.

STEEL

Remove rust and prime with a suitable Taubmans iron & steel primer or White Knight Rust Guard® Metal Primer.

ZINCALUME® STEEL

Wash with water and mild detergent. Surface must be clean and dry. Apply one coat of Taubmans 3 in 1 Prep.

PREVIOUSLY PAINTED	Remove all loose and flaking paint. Apply Taubmans 3 in 1 Prep to aged enamel systems to provide intercoat adhesion.
TEMPERATURE MIN	10 (°C)
TEMPERATURE MAX	35 (°C)
RECOATTEMPDEGREES	25 (°C)
RECOATHUMIDITYPERCENTAGE	50 (%)
RAINWATER COLLECTION PREP	Ensure surface is clean, dry and free from all dirt, dust, grease, oil, rust and any other surface contamination. Prior to painting, disconnect all down pipes or methods of water collection. Do not apply a primer. Leave downpipes disconnected for at least 1 week after painting. Rinse painted roof thoroughly with a hose, allow to dry, and repeat. Reconnect downpipes. Alternatively downpipes may be reconnected after heavy rainfall (>10mm in 24 hours).

APPLICATION

WET FILM THICKNESS	60 - 65 microns
DRY FILM THICKNESS	25 - 30 microns
STIRRING	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
BRUSH, ROLLER, SPRAY	Apply one or two coats (as per recommendation) by roller, brush or spray gun, with the recommended RECOAT time between each coat (refer to product spec). Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.
NAP ROLLER	10mm - 12mm Pile Roller
COVERAGE	Up to 16m ² /litre.
APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS	10
APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS	35
COATS REQUIRED	Two

PRECAUTIONS

GENERAL SAFETY INFORMATION	<p>WALL PAINTS</p> <p>SAFETY</p> <p>Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p>
-----------------------------------	---

DATASHEET

CEILING

SAFETY

Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

FIRST AID INFORMATION

IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.

EYE CONTACT - Flush with plenty of water. Always seek medical advice.

SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.

INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.

AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686
Further information: www.taubmans.com.au

ENVIRONMENT INFORMATION

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

ENVIRONMENT & SAFETY

WARRANTY INFORMATION

Taubmans SunProof Exterior is guaranteed against blistering, flaking or peeling if applied on suitable and properly prepared surfaces according to printed directions. This guarantee applies to the owner of the house/property to which the paint has been applied and is available as long as the owner owns and lives in the house/property. The benefits provided under this guarantee are not transferable. Proof of purchase is required. This guarantee is given by PPG Industries Australia Pty Limited. This guarantee only applies to residential properties within Australia. This guarantee applies to defects in the manufacture or formulation of the paint and does not cover paint failure caused by factors beyond our control. If this guarantee is not met, we will replace the paint or refund your money. We are not liable for the cost of labour or any other direct or indirect loss or damage arising from a breach of this guarantee. Customers are responsible for all costs of claiming under this guarantee. To claim, customers must write to us or call our Customer Service number to request a claim form. The benefits provided by this guarantee are in addition to other rights and remedies under the law. If you are a consumer within the meaning of the Australian Consumer Law: Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au