

DATASHEET

Taubmans Professional Exterior Low Sheen

TAUBMANS

Product Code:
278710



Taubmans Professional Exterior Low Sheen

Taubmans Professional Exterior Low Sheen is a premium water-based, self-priming paint, specially developed for the professional painter to provide a luxurious application feel. It delivers excellent UV protection, coverage, washability, and a professional finish.

USES

Ideal for all exterior walls, cement render / masonry, trim, roofs, timber, galvanised iron, PVC piping and steel.

FEATURES AND BENEFITS

SELF-PRIMING	In most cases, removes the need for a prep coat
DIRT SHEDDING FORMULA	Protects surfaces and keeps them looking newer for longer by easily washing away dirt and pollutants from the surface
UV PROTECTION	Blocks out harmful UV rays for longer lasting results
WATER BASED FORMULA	Easy clean up with water
FAST DRYING	Assist project completion timelines with fast drying properties
EASY TO APPLY	Holds a wet edge longer to minimise lap marks and create a smooth uniform finish.
AUSTRALIAN MADE	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
TINTABLE	Tintable to over 10,000 colours. Order A4 samples or brush outs online at https://www.taubmans.com.au/specifiers/explore#search

PRODUCT SPECIFICATIONS

4L AVAILABLE SIZES	4L
---------------------------	----

DATASHEET

10L AVAILABLE SIZES	10L
15L AVAILABLE SIZES	15L
ACCENT BASE	Tint your desired colour from an Accent base
NEUTRAL BASE	Tint your desired colour from a Neutral base
WHITE BASE	Tint your desired colour from a White base
CLEAN UP	Water
SDS	SDS available from the Taubmans Website taubmans.com.au
GLOSS LEVEL	10-15 at 60° (% at a 60 degree angle)
DRY TIMES: RECOAT	2 hours
DRY TIMES: TOUCH DRY	30 mins
VOC LEVELS	37 g/Litre

SURFACE PREPARATION

RECOAT HUMIDITY PERCENTAGE	50 (%)
RECOAT TEMP DEGREES	25 (°C)
TEMPERATURE MIN	10 (°C)
TEMPERATURE MAX	35 (°C)

APPLICATION

BRUSH, ROLLER, SPRAY	Apply one or two coats (as per recommendation) by roller, brush or spray gun, with the recommended RECOAT time between each coat (refer to product spec). Paint the corners and edges with a narrow brush. Roll up to the edges using a quality synthetic or lambswool 10 - 12mm nap roller.
COATS REQUIRED	2
NAP ROLLER	10mm - 12mm Pile Roller
STIRRING	Stir paint with a wide flat stirrer in a circular lifting motion for at least 5 minutes before use. It is a requirement to stir paint before use to ensure that the colour tints are dispersed evenly throughout the paint. Continue stirring at regular intervals during application. Where more than one can of the same colour and product is required for a job, mix the contents of all the cans together to ensure colour consistency
DRY FILM THICKNESS	25 - 30 microns
WET FILM THICKNESS	60 -65 microns
COVERAGE	Up to 16 square metres per litre (depending on substrate).

DATASHEET

PRECAUTIONS

GENERAL SAFETY INFORMATION

WALL PAINTS

SAFETY

Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes; wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

CEILING

SAFETY

Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.

ENVIRONMENT INFORMATION

Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

FIRST AID INFORMATION

IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.

EYE CONTACT - Flush with plenty of water. Always seek medical advice.

SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.

INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.

AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au

ENVIRONMENT & SAFETY

WARRANTY INFORMATION

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au