

DATASHEET

Taubmans Armawall Trowel 1.5mm

TAUBMANS

Product Code:
305018



Taubmans Armawall Trowel 1.5mm

Taubmans Armawall Trowel On 1.5mm texture coating is a second step in the Armawall Texture Coating System and provides one of the base textures. Trowel On 1.5mm finish is a durable, high build acrylic texture finish with 1.5mm aggregates. Applied by trowel and finished with a polystyrene float, that gives Armawall Trowel On finish its distinctive texture patterns. Trowel 1.5mm is generally overcoated with Armawall Impact, Armawall Satin, Armawall Armashield or Armawall Roll on Membrane.

USES

Exterior cement render, masonry, bricks and blockwork, Fibre Cement Sheeting and AAC

FEATURES AND BENEFITS

FINISH	Trowel Finish – Attractive, contemporary, aesthetic appearance
PROVEN PERFORMANCE	Proven performance in all climates
VAPOR PERMEABILITY	Allows substrate to breathe to reduce moisture entrapment
AUSTRALIAN MADE	Our Aussie Heritage: Since our inception over a century ago, we've been proudly manufacturing paint on our Aussie shores. We're proud to be an Australian manufacturing success, with plants in Villawood NSW, and Clayton VIC.
WATER BASED FORMULA	Easy clean up with water

PRODUCT SPECIFICATIONS

CLEAN UP	Water, away from drains and watercourses
PROFILE	Medium
SPREAD RATE	0.8 m ² /litre
MATT	Can be applied to uneven surfaces in order to hide imperfections. May mark more easily than high sheen products, so is therefore not recommended for high traffic areas.

DATASHEET

Ideal for interior walls; an ultra-washable, stain resistant matt finish.

Ideal for exterior walls, cement render / masonry, trim, timber, galvanised iron, PVC piping and steel. Not suitable for surfaces used to collect drinking water

VOC LEVELS	< 1g/Litre
DRY TIMES: TOUCH DRY	60 mins
DRY TIMES: RECOAT	72 hours
15L AVAILABLE SIZES	15L
SDS	SDS available from the Taubmans Website taubmans.com.au
EXTENSIVE COLOUR RANGE	Tintable to over 10,000 colours. Order A4 samples or brush outs online at https://www.taubmans.com.au/specifiers/explore#search
WHITE BASE	Tint your desired colour from a White base

SURFACE PREPARATION

SURFACE PREPARATION	Surface preparation is the responsibility of the Applicator, Builder, Renovator or Main Contractor. Armawall Surface Preparation Products are designed to perform at their optimum when used as part of an Armawall Texture Coating System. New cement render, masonry and concrete surfaces should be allowed to cure for 28 days. Off form concrete should be thoroughly cleaned by acid etching, water or sand blasting to ensure all bond breaker oils are removed. All masonry surfaces should be primed with Armawall Primer (thinned 50-100% with water) prior to the application of Armawall Trowel-On. Seal tilt slab concrete and CFC with Armawall Sealer/ Bonder thinned 50% with GTA007 to ensure adhesion of topcoats. Previously painted surfaces in sound condition should be scrubbed down with detergent and fresh water, fresh water washed and allowed to dry. Previously painted enamel surfaces should be undercoated with Taubmans Tradecoat. Surface irregularities such as blow holes and profile defects may require patching with Armawall Filler or Patch prior to system application.
SUBSTRATE MOISTURE CONTENT (ARMAWALL)	Moisture content of the substrate must be no greater than 15% wood-moisture-equivalent (WME) prior to or during application, to ensure optimal coating system performance
TEMPERATURE MIN	10 (°C)
TEMPERATURE MAX	35 (°C)
RECOATTEMPDEGREES	25 (°C)
RECOATHUMIDITYPERCENTAGE	50 (%)

APPLICATION

STIRRING RECOMMENDATION	Stir Armawall Trowel-On prior to use
ODOUR	Low
APPLICATION	This product is applied with a steel trowel and scratched off vertically (or using a circular motion "swirl") with a polystyrene float to produce the texture finish
WET FILM THICKNESS	Variable
DRY FILM THICKNESS	1.5mm (Variable)

DATASHEET

NAP ROLLER	Steel Trowel
STAINLESS STEEL TROWEL POLYSTYRENE FLOAT	Working in an upward action with the trowel, hold trowel & material against wall and evenly apply material. Now working across the wall, in a horizontal action continue to spread the material evenly. This will also help even out trowel shudder marks. Once you start to see the tips of the aggregate correct depth has been reached. To create the Vertical style of finish, take the polystyrene float and pass lightly over the texture in a VERTICAL ACTION working top to bottom in short sharp passes. To create the circular style of finish, take the polystyrene float and pass lightly over the texture in a CIRCULAR ACTION working left to right in small circle passes.
COVERAGE	0.8m ² /litre
APPLICATION TEMPERATURE MINIMUM DEGREES CELCIUS	10
APPLICATION TEMPERATURE MAXIMUM DEGREES CELCIUS	35
COATS REQUIRED	One or Two

PRECAUTIONS

GENERAL SAFETY INFORMATION	<p>WALL PAINTS</p> <p>SAFETY</p> <p>Keep out of reach of children. Keep lid on when not in use. Avoid contact with skin and eyes: wear safety glasses and impervious gloves. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p> <p>CEILING</p> <p>SAFETY</p> <p>Keep out of reach of children. Keep lid on when not in use. Do not thin for roller/brush application. Avoid contact with eyes: always wear safety glasses for eye protection when painting ceilings and do not paint directly overhead. Wear overalls and impervious gloves to avoid skin and clothing contact. Ensure area is well ventilated, wear a mask if spraying. Wash hands with soap and water after use.</p>
FIRST AID INFORMATION	<p>IF SWALLOWED - Do NOT induce vomiting. Seek medical advice immediately.</p> <p>EYE CONTACT - Flush with plenty of water. Always seek medical advice.</p> <p>SKIN CONTACT - Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water.</p> <p>INHALATION - Remove to fresh air, seek medical advice if breathing is laboured.</p> <p>AUSTRALIA - 24 hour Medical Emergency Response Service: 1800 883 254 Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au</p>
ENVIRONMENT INFORMATION	Do not pour leftover paint down the drain. Dispose of contents and container in accordance with all local, regional, national and international regulations. For responsible disposal of paint and packaging visit paintback.com.au

DISCLAIMER

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Taubmans Customer Service. PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Taubmans Customer Service: 131 686 Further information: www.taubmans.com.au